



ARP GROUP

DRUŠTVO ZA USLUGE, PROJEKTOVANJE I INŽENJERING

ARP GROUP doo
Gandijeva 99a
11070 Novi Beograd
PIB:104411728
[mail:office@arpgroup.rs](mailto:office@arpgroup.rs)

www.arpgroup.rs
Tel: 011/31 81 733
Mob:064/22 56 714
Verzija: 10.08.2021.

CENOVNIK D-LINK MREŽNE OPREME

Važi od : 10.08.2021


D-Link[®]
Building Networks for People

SADRŽAJ

SWITCHEVI	3
NEUPRAVLJIVI (Unmanaged)	3
NEUPRAVLJIVI (Unmanaged) POE	3
UPRAVLJIVI (Managed) PoE	4
INDUSTRIJSKI	5
RUTERI	5
ACCESS POINTI	6
SMART HOME	6
PROFESIONALNA Wi-Fi OPREMA	7
OPTIČKI SFP MODULI	8




NEUPRAVLJIVI (Unmanaged) SWITCHEVI



Model	Kat. Broj	Opis	CENA EUR (gotovinski)	CENA EUR (račun bez PDV)
DES-1024D <i>24port Fast Ethernet 10/100 Mbps Desktop / Rackmount</i>	3416	 <p>24 Portova Megabitni Switch 24x 100 Mbps Ports Standardi : IEEE 802.1p, IEEE 802.3, IEEE 802.3u, IEEE 802.3x, Dimenzije: 280 x 125.8 x 44 mm</p>	53,72	44,77




NEUPRAVLJIVI (Unmanaged) POE SWITCHEVI



DES-1005P <i>5port Fast Ethernet 10/100 Mbps 1xPoE Port, 15,4W</i>	3413	 <p>5 Porta Megabitni PoE switch 5x 10/100 Mbps Fast Ethernet ports 1x PoE port Standardi : IEEE 802.1p, IEEE 802.3, IEEE 802.3af, IEEE 802.3u, IEEE 802.3x Switching Capacity: 1 Gbps PoE Power Budget Max. 15.4 W Dimenzije: 140 x 85 x 28 mm Desktop</p>	51,76	43,13
DGS-1008P <i>8port Gigabit 10/100/1000 Mbps 4xPoE Port, 52W</i>	3407	 <p>8 Porta Gigabitni PoE switch 8x 10/100/1000 Mbps Gigabit ports 4x PoE ports Standardi : IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3u, IEEE 802.3x, Switching Capacity: 16 Gbps PoE Power Budget Max. 52 W Dimenzije: 190 x 120 x 38 mm Desktop</p>	88,49	73,74
DES-1018P <i>18port 10/100 Fibre Uplinks 8xPoE Port, 80W, 8x10/100 Ports, 2x SFP</i>	5704	 <p>16 Porta Megabitni PoE Switch 2x Combo 1000Base-T/SFP ports 16x PoE ports PoE Power Budget Max. 246W Dimenzije: 280 x 210 x 44 mm Desktop / Rackmount</p>	328,58	273,82

UPRAVLJIVI (Managed) PoE SWITCHEVI



Model	Kat. Broj	Opis	CENA EUR (gotovinski)	CENA EUR (račun bez PDV)
DGS-3120-24SC-SI	6081	 <p>24 Gigabit xStack L2+ Managed Gigabit Switches • 16 SFP Ports • 8 Combo 10/100/1000Base-T/SFP Ports Switching Capacity: 88 Gbps SD card slot Dimenzije: 440 x 210 x 44 mm Desktop / Rackmount</p>	869,94	724,95
<i>xStack L2+ Managed Gigabit Switches</i>				
DPS-500A	5447	 <p>Redudantno napajanje Izlazna snaga: 140 W Ulazni Napon: 90 to 264 V AC Ulazna frekvencija: 47 to 63 Hz Max ulazna struja: 1A at 240 V AC Max Inrush current: 60 A at 230 V AC Dimenzije: 172 x 257 x 43 mm</p>	366,46	305,38
<i>Modular Redundant Power Supplies</i>				
DPS 800	5487	 <p>Rack mount Nosač za dva redudantna napajanja</p>	124,45	103,71
<i>Nosač za dva redudantna napajanja</i>				

INDUSTRIJSKI SWITCHEVI



DIS-100G-5SW

5455



4 x 100/1000Base-T ports,
1 x 100/1000BaseSFP slots
Unmanaged plug-and-play simplicity
Withstands extreme temperatures
Certified for vibration, shock, free-fall, NEMA TS2 Section 2, EMC

262,12

218,43

Industrial Gigabit Unmanaged Switch with SFP slot

DIS-100G-5PSW

5706



4 x 100/1000Base-T ports PoE,
1 x 100/1000BaseSFP slots
PoE budget: 120W
Unmanaged plug-and-play simplicity
Withstands extreme temperatures
Certified for vibration, shock, free-fall, NEMA TS2 Section 2, EMC


463,08

385,90

Industrial Gigabit PoE Unmanaged Switch with SFP slot

RUTERI








Model	Kat. Broj	Opis	CENA EUR (gotovinski)	CENA EUR (račun bez PDV)
 DWM-312 4G LTE M2M Router	5456	Speeds up to 150 Mbps Fast Ethernet Dual-SIM slot Zinc-plated steel case for durability Withstands extreme temperatures and humidity	343,56	286,30



ACCESS POINT

D-Link
Building Networks for People

Model	Kat. Broj	Opis	CENA EUR (gotovinski)	CENA EUR (račun bez PDV)
 DAP-2020 <i>Wireless N Access Point</i>	5389	  <p>Wireless N Access Point Mrežni standardi: 802.11 b/g/n do 300Mbps Interfejsi 1xLAN, QoS 2x5dBi antene, na 2,4Ghz Režimi rada: Access point, Bridge, Repeater Enkripcije: 64/128-bit WEP data encryption WPA-PSK, WPA2-PSK, WPA-EAP, WPA2-EAP, TKIP, AES Dimenzije: 147.5 x 113 x 31.5 mm Temperatura ambijenta rada: 0 to 40 °C</p>	35,42	29,52
DAP-2662 <i>Plafonski Access Point</i>	6491	 <p>Wireless AC1200 Wave 2 Dual Band PoE Access Point 2x2 MU-MIMO Režimi-Access Point, Wireless Client, WDS, WDS with AP Mrežni standardi: IEEE802.11a/b/g/n/ac Wave 2 wireless Interfejsi 1x Gigabit LAN PoE</p> <ul style="list-style-type: none"> • 4 internal dual-band 3 dBi omni antennas • Two internal 3 dBi for 2.4 GHz • Two internal 4 dBi for 5 GHz <p>2.4 GHz band: 2.4 to 2.4835 GHz 5 GHz band: 5.15 to 5.35 GHz, 5.47 to 5.85 GHz 2.4 GHz • Up to 300 Mbps 5 GHz • Up to 867 Mbps Dimenzije: • 170 x 170 x 28 mm Temperatura ambijenta rada: 0 to 40 °C</p>	205,00	170,83
DNH-100	6492	 <p>Nuclias Connect Hub DNH-100 Upravljanje do 100 AP istovremeno ili pojedinačno bez potrebe za dodatnim serverom Upravljanje softverom Nuclias Connect Upravljanje više VLAN-ova za unapređeno upravljanje mrežom i podešavanjem SSID-a za bolju kontrolu -1000Base-T Ethernet Port, USB 3.0 Port, Micro SD Slot Izveštavanje o saobraćaju i analitika Daljinsko podešavanje AP monitoring: Managed AP, Rogue AP Authentication fail AP, Standalone AP Podrška za interfejs komandne linije (CLI) Podrška za NAT Passthrough koja omogućava upravljanje s više mesta</p>	144,00	120,00

SMART HOME








D-Link
Building Networks for People

Model	Kat. Broj	Opis	CENA EUR (gotovinski)	CENA EUR (račun bez PDV)
 PAMETNA UTICNICA DSP-W115/E	5339	 <p>Upoznajte D-Link WiFi pametnu utičnicu</p> <ul style="list-style-type: none"> * Plug & Play povezivanje na kućnu WiFi Mrežu * Upali / Ugasi preko mobilnog telefona * Napravite dnevni ili nedeljni raspored paljenja i gašenja u određenom vremenskom periodu * Sprečite pregrevanje uređaja * Radi preko Google Home, Amazon Echo I IFTTT protokola 	34,96	29,13

220V WiFi Smart Utičnica

PROFESIONALNA Wi-Fi OPREMA

D-Link
Building Networks for People

Model	Kat. Broj	Opis	CENA EUR (gotovinski)	CENA EUR (račun bez PDV)
 DWL-6610AP	5261	 <p>Unified Wireless AC dual band AP) Wi-Fi interface: 802.11b/g/n 2.4 GHz wireless 802.11ac/a/n 5 GHz wireless Interface: 10/100/1000BASE-T LAN (PoE) port IEEE 802.3af Power over Ethernet (PoE) Interne omni antene 4 dBi za 5 GHz, 4 dBi za 2.4 GHz 32 SSIDs 802.1Q VLAN Dimenzije: 205 x 39 mm</p>	227,24	189,37
<p><i>Wireless AC1200 Dual Band Unified Access Point</i></p>				
 DAP-3662	4283	 <p>Wireless AC1200 Concurrent Dual-Band Outdoor IEEE 802.11ac wireless Do 1200 Mbps 2XGigabit LAN ports Standardi: IEEE 802.11a/b/g/n/ac1 IEEE 802.3u/ab/af Frekvencije: 2.4 GHz band: 2.4 GHz to 2.4835 GHz 5 GHz: 5.15 do 5.35 GHz, 5.47 do 5.85 GHz2 IP68 Vodootporno kućište Vodootporno za temperature između -30do60°C Gore-Tex® Technology omogućava da ne dolazi do kondenzacije unutar uređaja. 802.3af PoE Dimenzije: 277 x 240 x 50 mm</p>	283,20	236,00
<p><i>Wireless AC1200 Concurrent Dual-Band Outdoor PoE Access Point</i></p>				
 DAP-3320	4166	  <p>Wireless N PoE Outdoor Access Point. 10dBi Sektor antena 2,4Ghz 802.11.n / b / g. Dimenzije: 48 x 96 x 165 mm Wireless N PoE 10dBi Sektor antena 2,4Ghz 802.11.n / b / g. Interfejs: 802.11n/g/b wireless, Reset Button 10/100BaseT PoE Ethernet Port, Operativni Modovi: AP, WDS, WDS with AP, Wireless Client Dimenzije: 105.43 x 228.6 x 35.86 mm</p>	80,40	67,00
<p><i>Wireless N PoE Outdoor Access Point</i></p>				

OPTIČKI SFP MODULI



Model	Kat. Broj	Opis	CENA EUR (gotovinski)	CENA EUR (račun bez PDV)
DEM-310GT	4747	 <p>1000Base-LX port (IEEE 802.3z standard) Duplex LC connector Full duplex operation 802.3x flow control support Fibre type: 9um single-mode fibre, up to 10 km. Wavelength: 1310 nm Power support: 3.3 V Hot pluggable MSA Compliant RoHS Compliant</p>	73,93	61,61
<i>GBIC Module for 1000BaseLX (LC Duplex)</i>				
DEM-431XT	5448	 <p>Standard Compliance • IEEE-802.3ae, 10GBASE-SR Transceiver Type - SFP+ Fibre Channel FC-PI Standard -1200-Mx-SN-I Fiber Media Support - Multi-Mode Distance Capacity: • 62.5 µm, 160 MHz-km: 26 m • 62.5 µm, OM1 200 MHz-km: 33 m • 50 µm, 400 MHz-km: 66 m • 50 µm, OM2 500 MHz-km: 82 m • 50 µm, OM3 2000 MHz-km: 300 m Speed - 10 Gbps Single/Bi Direction - Single-direction Wavelength - 850 nm Power support: 3.3 V Hot pluggable MSA Compliant RoHS Compliant</p>	293,84	244,87
<i>SFP+ 10GBASE SR Multi Mode Fibre Transceiver (300m)</i>				
DEM-432XT	6082	 <p>Standard Compliance • IEEE-802.3ae • 10GBASE-LR Transceiver Type - SFP+ Fibre Channel FC-PI Standard -1200-SM-LL-L Fiber Media Support - • Single-Mode Distance Capacity: 10 km Brzina - 10 Gbps Konektor- Duplex LC konektor Single/Bi Direction - Single-direction Wavelength - 1310 nm Single-mode 9/125 um fiber Power support: 3.3 V Hot pluggable MSA Compliant RoHS Compliant</p>	554,03	461,69