






ARP GROUP

DRUŠTVO ZA USLUGE, PROJEKTOVANJE I INŽENJERING

ARP GROUP doo
Gandijeva 99a
11070 Novi Beograd
PIB:104411728
[mail:office@arpgroup.rs](mailto:office@arpgroup.rs)
www.arpgroup.rs
Tel: 011/31 81 733
Mob:064/22 56 714
Verzija: 04.11.2021.

HIKVISION AKTIVNA MREŽNA OPREMA

Važi od: 04.11.2021

SWITCH-evi			HIKVISION®	
NAZIV ARTIKLA	Kat. broj	OPIS	CENA EUR(gotovinski)	CENA EUR (račun bez PDV)
DS-3E0108D-E Megabitni Switch  HIKVISION®	6733	Portovi: 8 x 10/100 Mbps RJ45 ports Standardi: IEEE 802.3, IEEE 802.3u, IEEE 802.3x MAC address table: 1 K Switching capacity: 1.6 Gbps Packet forwarding rate: 1.1904 Mpps Materijal kućišta: ABS Težina: 0.041 kg Dimenzije: 124 x 59 x 23.2 mm Radna temperatura: 0°C-40°C Napajanje: 5 V DC, 0.6 A	10.80	9.00
DS-3E0505D-E Gigabitni Switch  HIKVISION®	6735	Portovi: 5 x 10/100/1000 Mbps RJ45 ports Standardi: IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3ab MAC address table: 2 K Switching capacity: 10 Gbps Packet forwarding rate: 7.44 Mpps Materijal kućišta: ABS Težina: 0.03 kg Dimenzije: 92.8 x 65.8 x 22.8 mm Radna temperatura: 0°C-40°C Napajanje: 5 VDC, 0.6 A	18.00	15.00
DS-3E0508D-E Gigabitni Switch  HIKVISION®	6731	Portovi: 8 x 10/100/1000 Mbps RJ45 ports Standardi: IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3ab MAC address table: 4 K Switching capacity: 16 Gbps Packet forwarding rate: 11.904 Mpps Materijal kućišta: ABS Težina: 0.065 kg Dimenzije: 142 x 90 x 23 mm Radna temperatura: 0°C-70°C Napajanje: 9 VDC, 0.6 A	25.20	21.00

NAZIV ARTIKLA

Kat. broj

OPIS

CENA
EUR(gotovinski)CENA EUR
(račun bez PDV)**DS-3E0505-E
Gigabitni Switch**

HIKVISION®

Portovi: 5 x 10/100/1000 Mbps RJ45 ports Full duplex, MDI/MDI-X adaptive
 Standardi: IEEE 802.3, IEEE 802.3u, IEEE 802.3x
 MAC address table: 2 K
 Switching capacity: 10 Gbps
 Packet forwarding rate: 7.44 Mpps
 Interna keš memorija: 1 Mbits
 Materijal kućišta: Metalno kućište
 Težina: 0.15 kg
 Dimenzije: 103 mm x 25.6 mm x 61.1 mm
 Radna temperatura: 0°C~40°C
 Napajanje: 5 VDC, 1 A

6775

19.20

16.00

**DS-3E0508-E(B)
Gigabitni Switch**

HIKVISION®

Portovi: 8 x 10/100/1000 Mbps RJ45 ports Full duplex, MDI/MDI-X adaptive
 Standardi: IEEE 802.3, IEEE 802.3u, IEEE 802.3x
 MAC address table: 4 K
 Switching capacity: 16 Gbps
 Packet forwarding rate: 11.904 Mpps
 Interna keš memorija: 1.5 Mbits
 Materijal kućišta: Metalno kućište
 Težina: 0.25 kg
 Dimenzije: 145 mm x 25.6 mm x 68.4 mm
 Radna temperatura: 0°C~40°C
 Napajanje: 5 VDC, 1 A

6770

30.00

25.00

**DS-3E0516-E(B)
Gigabitni Switch**

HIKVISION®

Portovi: 16 x 10/100/1000 Mbps RJ45 ports Full duplex, MDI/MDI-X adaptive
 Standardi: IEEE 802.3, IEEE 802.3u, IEEE 802.3x
 MAC address table: 8 K
 Switching capacity: 32 Gbps
 Packet forwarding rate: 23.808 Mpps
 Interna keš memorija: 4.1 Mbits
 Materijal kućišta: Metalno kućište
 Težina: 1.2 kg
 Dimenzije: 257 mm x 44.5 mm x 175.8 mm
 Radna temperatura: 0°C~40°C
 Napajanje: 220 VAC, 50/60 Hz, Max. 0.3 A

6769

78.00

65.00

**DS-3E0524-E(B)
Gigabitni Switch**

HIKVISION®

Portovi: 24 x 10/100/1000 Mbps RJ45 ports Full duplex, MDI/MDI-X adaptive
 Standardi: IEEE 802.3, IEEE 802.3u, IEEE 802.3x
 MAC address table: 8 K
 Switching capacity: 48 Gbps
 Packet forwarding rate: 35.712 Mpps
 Interna keš memorija: 4.1 Mbits
 Materijal kućišta: Metalno kućište
 Težina: 1.6 kg
 Dimenzije: 335 mm x 44.5 mm x 175.8 mm
 Radna temperatura: 0°C~40°C
 Napajanje: 220 VAC, 50/60 Hz, Max. 0.7 A

6772

102.00

85.00

NAZIV ARTIKLA

Kat. broj

OPIS

CENA
EUR(gotovinski)CENA EUR
(račun bez PDV)**DS-3E1105P-EI**
Smart PoE Switch

HIKVISION®

7132

Portovi: 4 × 100 Mbps PoE RJ45 i 1 × 100 Mbps RJ45 port
 Možete pregledati topologiju mreže, pratiti zdravlje mreže i primati alarme uređaja u realnom vremenu, što uveliko smanjuje troškove mreže rada i održavanje.
 Standardi: IEEE 802.3, IEEE 802.3u, IEEE 802.3x, PoE IEEE 802.3af, IEEE 802.3at
 MAC address table: 2 K
 Switching capacity: 1 Gbps
 Packet forwarding rate: 0.744 Mpps
 Interna keš memorija: 768 Kbits
 Visoko prioritetni portovi 1 i 2. Portovi za udaljene transmisije 1 i 4.
 AF/AT kamera može da dosegne do 300 m u produženom režimu.
 Zaštita od prenapona od 6 KV za PoE portove.
 PoE power budget: 60 W, Max. 30 W za jedan port
 Napajanje: 48 VDC, 1.35 A
 Dimenzije: 105 mm × 27.6 mm × 83.1 mm
 Težina: 0.22 kg

43.20

36.00

NAZIV ARTIKLA

Kat. broj

OPIS

CENA
EUR(gotovinski)CENA EUR
(račun bez PDV)

DS-3E0105P-E/M Megabitni PoE Switch



HIKVISION®

5833

4 x 100M PoE ports and 1 x 100M Ethernet port
Podržava: IEEE802.3at/af, IEEE 802.3, IEEE 802.3u and IEEE 802.3x
Distanca prenosa do 250m sa uključenim extend on prekidačem uz brzinu od 10Mb/s.
Crveni portovi su većeg prioriteta.
6kV zaštita od prenapona
Maksimalna snaga porta: 30W
PoE budžet: 35W
Dimenzije: 105 x 27,6 x 83,1 mm

36.00

30.00

DS-3E0109P-E/M Megabitni PoE Switch



HIKVISION®

5834

8 x 100M PoE ports and 1 x 100M Ethernet port
Podržava: IEEE802.3at/af, IEEE 802.3, IEEE 802.3u and IEEE 802.3x
Distanca prenosa do 250m sa uključenim extend on prekidačem uz brzinu od 10Mb/s.
Crveni portovi su većeg prioriteta.
6kV zaštita od prenapona
Maksimalna snaga porta: 30W
PoE budžet: 60W
Dimenzije: 170 x 27,6 x 93,1 mm

73.20

61.00

DS-3E0106HP-E Megabitni PoE Switch



HIKVISION®

6683

Portovi:
1 x 10/100 Mbps Hi-PoE port,
3 x 10/100 Mbps PoE ports,
2 x 10/100 Mbps RJ45 ports
Inteligentno PoE rukovanje, Distanca do 300m transmisije, 6KV zaštita, Dizajniran za video transmisiju
Standardi: IEEE 802.3, IEEE 802.3u, IEEE 802.3x
MAC address table: 2 K
Switching capacity: 1.2 Gbps
Packet forwarding rate: 0.893 Mpps
Interna keš memorija: 768 Kbits
PoE standardi:
port 1 - IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt
port 2-4 - IEEE 802.3af, IEEE 802.3at
PoE power budget: 60 W
Dimenzije: 145 mm x 25.6 mm x 68.45 mm
Težina: 0.24 kg

45.60

38.00

DS-3E0505HP-E Gigabitni PoE Switch



HIKVISION®

6981

Portovi:
3 x gigabit PoE ports,
1 x gigabit Hi-PoE port,
1 x gigabit RJ45 port
Distanca do 300m transmisije (port 3 i 4), 6KV zaštita, automatsko restartovanje kamere ukoliko ne radi
Standardi: IEEE 802.3, IEEE 802.3u, IEEE 802.3x, and IEEE 802.3ab
MAC address table: 2 K
Switching capacity: 10 Gbps
Packet forwarding rate: 7.44 Mpps
Interna keš memorija: 1 Mbits
PoE standardi:
port 1 - IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt
port 2-4 - IEEE 802.3af, IEEE 802.3at
PoE power budget: 60 W
Dimenzije: 121 mm x 88.1 mm x 27.6 mm
Težina: 0.27 kg

66.00

55.00

NAZIV ARTIKLA

Kat. broj

OPIS

CENA
EUR(gotovinski)CENA EUR
(račun bez PDV)

DS-3E0310HP-E Megabitni PoE Switch



HIKVISION®

6705

Portovi:
 1 × 10/100 Mbps Hi-PoE port,
 7 × 10/100 Mbps PoE ports,
 2 × 10/100/1000 Mbps RJ45 ports
 Inteligentno PoE rukovanje, Distanca do 300m transmisije, 6KV zaštita
 Standardi: IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3ab, and IEEE 802.3z
 MAC address table: 16 K
 Switching capacity: 5.6 Gbps
 Packet forwarding rate: 4.166 Mpps
 Interna keš memorija: 4 Mbits
 PoE standardi:
 port 1 - IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt
 port 2-8 - IEEE 802.3af, IEEE 802.3at
 PoE power budget: 110 W, Max. 90 W za jedan port
 Dimenzije: 217.6 mm × 27.8 mm × 103.35 mm
 Težina: 0.55 kg

132.00

110.00

DS-3E0510HP-E Gigabitni PoE Switch



HIKVISION®

6982

Portovi:
 6 × gigabit PoE ports,
 2 × gigabit Hi-PoE ports,
 1 × gigabit RJ45 port,
 Inteligentno PoE rukovanje, Distanca do 300m transmisije (port 7 i 8), 6KV zaštita
 Standardi: IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3ab, and IEEE 802.3z
 MAC address table: 4 K
 Switching capacity: 20 Gbps
 Packet forwarding rate: 14.88 Mpps
 Interna keš memorija: 1.5 Mbits
 PoE standardi:
 port 1-2 - IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt
 port 3-8 - IEEE 802.3af, IEEE 802.3at
 PoE power budget: 110 W, Max. 90 W za port 1 i 2
 Dimenzije: 217.6 mm × 108.55 mm × 27.8 mm
 Težina: 0.59 kg

156.00

130.00

DS-3E0318P-E Megabitni PoE Switch



HIKVISION®

4820

16 × 10/100 Mbps Auto MDX PoE
 2 × 1000 Mbps Combo port
 4kV zaštita od prenapona
 PoE budžet 230W
 Podržava 802.3 AF/AT standarde do 30W snage po portu
 Dimenzije: 440 x 285 x 43mm

252.00

210.00

NAZIV ARTIKLA

Kat. broj

OPIS

CENA
EUR(gotovinski)CENA EUR
(račun bez PDV)**DS-3E0520HP-E
Gigabitni PoE Switch**

HIKVISION®

Portovi:
 12 × Gigabit PoE ports, 4 × Gigabit Hi-PoE PoE ports,
 2 × Gigabit RJ45 port, 2 × Gigabit fiber optical ports
 Inteligentno PoE rukovanje, 6KV zaštita od prenapona
 Prenos velikog dometa do 300m za određene portove.
 PoE čuvar za automatsko otkrivanje i ponovno pokretanje kamera koje ne reaguju.
 Hi-PoE standardi: IEEE 802.3at/af/bt
 PoE standardi: IEEE 802.3at/af
 Standardi: IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3ab, and IEEE 802.3z
 MAC address table: 8 K
 Switching capacity: 40 Gbps
 Packet forwarding rate: 29.76 Mpps
 Interna keš memorija: 4.1 Mbits
 PoE power budget: 225 W
 Portovi 1-4: 90W max port snaga, portovi 5-16: 30W
 Dimenzije: 440 mm × 44 mm × 220.8 mm
 Težina: 2.79 kg

6955

348.00

290.00

**DS-3E0528HP-E
Gigabitni PoE Switch**

HIKVISION®

Portovi:
 20 × Gigabit PoE ports, 4 × Gigabit Hi-PoE PoE ports,
 2 × Gigabit RJ45 port, 2 × Gigabit fiber optical ports
 Inteligentno PoE rukovanje, 6KV zaštita od prenapona
 Prenos velikog dometa do 300m za određene portove.
 PoE čuvar za automatsko otkrivanje i ponovno pokretanje kamera koje ne reaguju.
 Hi-PoE standardi: IEEE 802.3at/af/bt
 PoE standardi: IEEE 802.3at/af
 Standardi: IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3ab, and IEEE 802.3z
 MAC address table: 8 K
 Switching capacity: 56 Gbps
 Packet forwarding rate: 41.664 Mpps
 Interna keš memorija: 4.1 Mbits
 PoE power budget: 370 W
 Portovi 1-4: 90W max port snaga, portovi 5-24: 30W
 Dimenzije: 440 mm × 44 mm × 220.8 mm
 Težina: 2.98 kg

6953

444.00

370.00

**DS-3E0326P-E
Megabitni PoE Switch**

HIKVISION®

Portovi:
 24 × 10/100 Mbps PoE RJ45,
 2 × Gigabit RJ45 port,
 Gigabit SFP fiber optical port
 4KV zaštita od prenapona
 Standardi: IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE802.3af, IEEE 802.3at, IEEE
 802.3x, IEEE802.3z
 PoE standardi: IEEE 802.3af, IEEE802.3at
 MAC address table: 4 K
 Switching capacity: 8.8 Gbps
 Packet forwarding rate: 6.55Mpps
 PoE power budget: 370W, Max. 30 W za jedan port
 Težina: 2.67 kg

6730

348.00

290.00

NAZIV ARTIKLA

Kat. broj

OPIS

CENA
EUR(gotovinski)CENA EUR
(račun bez PDV)**DS-3T0306HP-E/HS**
4 porta

HIKVISION®

6511

Broj portova (Uplink):1 × gigabit RJ45 port ,
1 × gigabit SFP Fiber Optical Port**Broj portova (Downstream):**3 × 100M PoE ports (30W), domet portova 3 i 4 do 300m
1 × Hi-PoE port (60W)**PoE power budget:** 60W**Switching kapacitet:** 4.8 Gbps**MAC address table:** 2 K**Propusnost:** 3.5712 Mpps**Memorijski buffer:** 1Mbit**Standardi:** IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z and IEEE 802.3ab,
IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt, IEEE 802.3af, IEEE 802.3at
u zavisnosti od porta**Režimi rada:** Standard mode (default), Extend mode, Isolation mode, PoE
watchdog mode**Zaštita od groma:** 6 KV za PoE portove**Napanjanje:** 48~57V DC**Radna temperatura:** -30 °C to 65 °C**Dimenzije:** 158 mm × 101.2 mm × 31.6 mm**Težina:** 0,35kg

94.80

79.00

DS-3T0310HP-E/HS
8 porta

HIKVISION®

6512

Broj portova (Uplink):1 × gigabit RJ45 port ,
1 × gigabit SFP Fiber Optical Port**Broj portova (Downstream):**6 × 100M PoE ports (30W), domet portova 7 i 8 do 300m
2 × Hi-PoE port (90W)**PoE power budget:** 110W**Switching kapacitet:** 5.6 Gbps**MAC address table:** 2 K**Propusnost:** 4.1664 Mpps**Memorijski buffer:** 1Mbit**Standardi:** IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z and IEEE 802.3ab,
IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt, IEEE 802.3af, IEEE 802.3at
u zavisnosti od porta**Režimi rada:** Standard mode (default), Extend mode, Isolation mode, PoE
watchdog mode**Zaštita od groma:** 6 KV za PoE portove**Napanjanje:** 48~57V DC**Radna temperatura:** -30 °C to 65 °C**Dimenzije:** 197 mm × 114.2 mm × 42.2 mm**Težina:** 0,565kg

134.40

112.00

NAZIV ARTIKLA

Kat. broj

OPIS

CENA
EUR(gotovinski)

CENA EUR
(račun bez PDV)

DS-3T0506HP-E/HS
4 porta



HIKVISION®

6519

Broj portova (Uplink):
2 × gigabit SFP Fiber Optical Port
Broj portova (Downstream):
3 × gigabit PoE ports (30W), do met portova 3 i 4 do 300m
1 × Hi-PoE port (60W)
PoE power budget: 60W
Switching kapacitet: 12 Gbps
MAC address table: 4 K
Propusnost: 8.928 Mpps
Memorijski buffer: 1.5 Mbits
Standardi: IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z and IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt, IEEE 802.3af, IEEE 802.3at u zavisnosti od porta
Režimi rada: Standard mode (default), Extend mode, Isolation mode, PoE watchdog mode
Zaštita od groma: 6 KV za PoE portove
Napanjanje: 48~57V DC
Radna temperatura: -30 °C to 65 °C
Dimenzije: 158 mm × 101.2 mm × 31.6 mm
Težina: 0.38 kg

126.00

105.00

DS-3T0510HP-E/HS
8 porta



HIKVISION®

6520

Broj portova (Uplink):
2 × gigabit SFP Fiber Optical Port
Broj portova (Downstream):
6 × gigabit PoE ports (30W), do met portova 7 i 8 do 300m
2 × Hi-PoE port (90W)
PoE power budget: 110W
Switching kapacitet: 20 Gbps
MAC address table: 4 K
Propusnost: 14.88 Mpps
Memorijski buffer: 1.5 Mbits
Standardi: IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z and IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt, IEEE 802.3af, IEEE 802.3at u zavisnosti od porta
Režimi rada: Standard mode (default), Extend mode, Isolation mode, PoE watchdog mode
Zaštita od groma: 6 KV za PoE portove
Napanjanje: 48~57V DC
Radna temperatura: -30 °C to 65 °C
Dimenzije: 197 mm × 114.2 mm × 42.2 mm
Težina: 0.585 kg

174.00

145.00

NAZIV ARTIKLA	Kat. broj	OPIS	CENA EUR(gotovinski)	CENA EUR (račun bez PDV)
HK-SFP-1.25G-1310-DF-MM SFP Module  	6521	Tip: MMF, duplex fiber, 62.5/125um, 50/125um Konektori: LC, komada 2 Brzina prenosa: 1250 Mbps Distanca: 0~1km Talasna dužina: Tx1310nm/Rx1310nm TX Power: -9~-3dBm RX Sens(Max.): -20dBm Radna temperatura: 0~70°C Relativna vlažnost: 30~80% Napajanje: DC 3.3V	31.80	26.50
HK-SFP-1.25G-20-1310-DF Single mode SFP Module  	6523	Tip: SMF, duplex fiber, 9/125um Konektori: LC, komada 2 Brzina prenosa: 1250 Mbps Distanca: 0~20km Talasna dužina: Tx1310nm/Rx1310nm TX Power: -9~-3dBm RX Sens(Max.): -20dBm Radna temperatura: 0~70°C Relativna vlažnost: 30~80% Napajanje: DC 3.3V	32.40	27.00
HK-SFP-1.25G-20-1310 SFP Module  	6522	Tip: SMF, Single fiber, 9/125um Konektori: LC, komada 1 Brzina prenosa: 1250 Mbps Distanca: 0~20km Talasna dužina: Tx1310nm/Rx1550nm TX Power: -9~-1dBm RX Sens(Max.): -21dBm Radna temperatura: 0~70°C Relativna vlažnost: 30~80% Napajanje: DC 3.3V <i>Napomena : 6522 i 6524 se kupuju u paru</i>	33.60	28.00
HK-SFP-1.25G-20-1550 SFP Module  	6524	Tip: SMF, Single fiber, 9/125um Konektori: LC, komada 1 Brzina prenosa: 1250 Mbps Distanca: 0~20km Talasna dužina: Tx1550nm/Rx1310nm TX Power: 9~-1dBm RX Sens(Max.): -21dBm Radna temperatura: 0~70°C Relativna vlažnost: 30~80% Napajanje: DC 3.3V <i>Napomena : 6522 i 6524 se kupuju u paru</i>	34.80	29.00