ARP GROUP
DRUŠTVO ZA USLUGE, PROJEKTOVANJE I INŽENJERING

**ARP GROUP doo**
**Gandijeva 99a**
**11070 Novi Beograd**
**PIB:104411728**
mail:office@arpgroup.rs
www.arpgroup.rs **Tel:**
**011/31 81 733**
**Mob:064/22 56 714**
**Verzija:09.01.2024.**

# *CENOVNIK UNIVIEW VIDEO NADZORA I PRATEĆE OPREME*

**Uniview Technologies**

# HDTVI - DVR (DIGITAL VIDEO RECORDERS) UNIVIEW

| NAZIV ARTIKLA | Kat. br. | Karakteristike | CENA EUR (gotovinski) | CENA EUR (racun bez PDV) |
|---|---|---|---|---|
| **XVR301-04G3** | 8037 | **XVR301-04G3**<br>**4-KANALNI HIBRIDNI SNIMAČ TVI,AHD, CVI,CVBS, IP**<br>**Rezolucija snimanja:** 5MP Lite/4MP Lite/1080P/720P/CIF<br>**Rezolucija snimanja IP kamera:** do 4mp (2 IP kamere ili svih 6)<br>**Video kompresija:** H.265, H.264<br>**Video/audio ulazi:** 4ch BNC, 1ch audio<br>**Video/audio izlazi:** HDMI/VGA (FULL HD), CVBS (960x576), 1ch audio<br>**Ulazno/Izlazni saobraćaj:** 16/48 Mbps<br>**Smart funkcije:** Motion detection, video loss<br>**Dodatni ulazi:** RJ45 mrežni ulaz, 2xUSB 2.0 interfejs<br>**Mrežni protokoli:** TCP/IP, P2P, UPnP, DHCP, HTTP, HTTPS, DNS, DDNS, SMTP<br>**Hard disk prostor:** 1 sata HDD do 8TB kapaciteta<br>**Opšte:** Napajanje 12V DC, Potrošnja 8W bez HDD,<br>**Radna temperatura:** -10 ºC ~ +55 ºC,<br>**Dimenzije:** 260mm ×226mm× 47mm (10.2" × 8.9"×1.8") | 87,60 | 73,00 |
| **XVR301-04Q** | 6717 | **XVR301-04Q**<br>**4-KANALNI HIBRIDNI SNIMAČ TVI,AHD, CVI,CVBS, IP**<br>**Rezolucija snimanja:** 8MP Lite/5MP Lite/4MP Lite /3MP/1080P/960P/720P/960H/4CIF/CIF<br>**Podržava** TVI,AHD, CVI, CVBS kamere do 8MP/15fps na kanalu 1<br>**Rezolucija snimanja IP kamera:** do 8mp (2 IP kamere ili svih 6)<br>**Video kompresija:** H.265, H.264<br>**Video/audio ulazi:** 4ch BNC, 1ch audio<br>**Video/audio izlazi:** HDMI/VGA (FULL HD), CVBS (960x576), 1ch audio<br>**Ulazno/Izlazni saobraćaj:** 48/60 Mbps<br>**Smart funkcije:** Motion detection, tampering, video loss detection, face detection, instrusion detection, cross line detection, audio detection, defocus detection, scene change detection<br>**Dodatni ulazi:** RJ45 mrežni ulaz, 2xUSB 2.0 interfejs, 1xRS485<br>**Mrežni protokoli:** TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE<br>**Hard disk prostor:** 1 sata HDD do 6TB kapaciteta<br>**Opšte:** Napajanje 12V DC, Potrošnja 8W bez HDD,<br>**Radna temperatura:** -10 ºC ~ +55 ºC,<br>**Dimenzije:** 260mm ×240mm× 46mm (10.2" × 9.4"×1.8") | 104,40 | 87,00 |
| **XVR301-04Q3** | 8036 | **XVR301-04Q3**<br>**4-KANALNI HIBRIDNI SNIMAČ TVI,AHD, CVI,CVBS, IP**<br>**Rezolucija snimanja:** 8MP Lite/5MP/5MP Lite/4MP Lite/1080P/720P/CIF<br>**Rezolucija snimanja IP kamera:** do 4mp (2 IP kamere ili svih 6)<br>**Video kompresija:** H.265, H.264<br>**Video/audio ulazi:** 4ch BNC, 1ch audio<br>**Video/audio izlazi:** HDMI (4K), VGA (FULL HD), CVBS (960x576), 1ch audio<br>**Ulazno/Izlazni saobraćaj:** 40/48 Mbps<br>**Smart funkcije:** Motion detection, video loss, audio detection<br>**Dodatni interfejsi:** RJ45 mrežni ulaz, 2xUSB 2.0 interfejs, 1xRS485, Alarmni ulaz/izlaz 4/1<br>**Mrežni protokoli:** TCP/IP, P2P, UPnP, DHCP, HTTP, HTTPS, DNS, DDNS, SMTP<br>**Hard disk prostor:** 1 sata HDD do 8TB kapaciteta<br>**Opšte:** Napajanje 12V DC, Potrošnja ≤ 10 W bez HDD,<br>**Radna temperatura:** -10 ºC ~ +55 ºC,<br>**Dimenzije:** 260mm ×226mm× 47mm (10.2" × 8.9"×1.8") | 123,60 | 103,00 |
| **XVR301-08Q3** | 8029 | **XVR301-08Q3**<br>**8-KANALNI HIBRIDNI SNIMAČ TVI,AHD, CVI,CVBS, IP**<br>**Rezolucija snimanja:** 8MP Lite/5MP/5MP Lite/4MP Lite/1080P/720P/CIF<br>**Rezolucija snimanja IP kamera:** do 8mp (4 IP kamere ili svih 12)<br>**Video kompresija:** H.265, H.264<br>**Video/audio ulazi:** 4ch BNC, 1ch audio<br>**Video/audio izlazi:** HDMI (4K), VGA (FULL HD), CVBS (960x576), 1ch audio<br>**Ulazno/Izlazni saobraćaj:** 40/64 Mbps<br>**Smart funkcije:** Motion detection, video loss, audio detection<br>**Dodatni interfejsi:** RJ45 mrežni ulaz, 2xUSB 2.0 interfejs, 1xRS485, Alarmni ulaz/izlaz 4/1<br>**Mrežni protokoli:** TCP/IP, P2P, UPnP, DHCP, HTTP, HTTPS, DNS, DDNS, SMTP<br>**Hard disk prostor:** 1 sata HDD do 8TB kapaciteta<br>**Opšte:** Napajanje 12V DC, Potrošnja ≤ 10 W bez HDD,<br>**Radna temperatura:** -10 ºC ~ +55 ºC,<br>**Dimenzije:** 260mm ×226mm× 47mm (10.2" × 8.9"×1.8") | 192,00 | 160,00 |

| | | | | |
|---|---|---|---|---|
| **XVR301-08Q**<br> | 6716 | **XVR301-08Q**<br>**8-KANALNI HIBRIDNI SNIMAČ TVI,AHD, CVI,CVBS, IP**<br>**Rezolucija snimanja:** 8MP Lite/5MP Lite/4MP Lite /3MP/1080P/960P/720P/960H/4CIF/CIF<br>**Podržava** TVI,AHD, CVI, CVBS kamere do 8MP/15fps na kanalu 1 i 2<br>**Rezolucija snimanja IP kamera:** do 8mp (4 IP kamere ili svih 12)<br>**Video kompresija:** H.265, H.264<br>**Video/audio ulazi:** 4ch BNC, 1ch audio<br>**Video/audio izlazi:** HDMI/VGA (FULL HD), CVBS (960x576), 1ch audio<br>**Ulazno/Izlazni saobraćaj:** 56/64 Mbps<br>**Smart funkcije:** Motion detection, tampering, video loss detection, face detection, instrusion detection, cross line detection, audio detection, defocus detection, scene change detection<br>**Dodatni ulazi:** RJ45 mrežni ulaz, 2xUSB 2.0 interfejs, 1xRS485<br>**Mrežni protokoli:** TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE<br>**Hard disk prostor:** 1 sata HDD do 6TB kapaciteta<br>**Opšte:** Napajanje 12V DC, Potrošnja 8W bez HDD,<br>**Radna temperatura:** -10 ºC ~ +55 ºC,<br>**Dimenzije:** 260mm ×240mm× 46mm (10.2" × 9.4"×1.8") | 174,00 | 145,00 |
| **NVR302-08U**<br> | 5850 | **NVR302-08U**<br>**8-KANALNI PENTABRIDNI HD SNIMAČ HDTVI, IP, CVBS, CVI, AHD**<br>**Rezolucija snimanja:** 8MP@8fps, 5MP@12fps, 4MP@15fps, 3MP@18fps, 2MP@25fps, 720P@30fps<br>**Frame rate po kanalima:** 2x4K@30, 2x6MP@30, 3x5MP@30, 4x4MP@30, 4x3MP@30, 6x3MP@25, 8x1080p@30, 16x720p@30<br>**Rezolucija snimanja IP kamera:** 8 IP kamere do 8mpx isključivanjem analognih kanala<br>**Ulazno/Izlazni saobraćaj:** 80/64 Mbps<br>**Video kompresija:** H.265/H.264 video kompresija,<br>**Video/audio ulazi:** 8ch BNC, 4ch audio RCA, 1xCVBS izlaz<br>**Video/audio izlazi:** HDMI/VGA (FULL HD), 1ch RCA<br>**Smart funkcije:** Alarm Notification/Alarm trigger(Face detection, Intrusion, cross line, Audio detection, Defocus,Scene Change)<br>**Alarmni Ulaz/Izlaz:** 8/4<br>**Dodatni ulazi:** RJ45 mrežni ulaz, 1xUSB 2.0 interfejs, 1xUSB 3.0 interfejs, 1x RS485<br>**Mrežni protokoli:** TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE<br>**Hard disk prostor:** 2 sata HDD do 10TB kapaciteta<br>**Opšte:** Napajanje 12V DC, Potrošnja 12W bez HDD,<br>**Radna temperatura:** -10 ºC ~ +55 ºC,<br>**Dimenzije:** 380mm ×315mm× 49mm, Težina 1.9Kg | 276,00 | 230,00 |
| **XVR302-16Q3**<br> | 8038 | **XVR302-16Q3**<br>**16-KANALNI HIBRIDNI SNIMAČ TVI,AHD, CVI,CVBS, IP**<br>**Rezolucija snimanja:** 8MP Lite/5MP Lite/4MP Lite /3MP/1080P/960P/720P/960H/4CIF/CIF<br>**Podržava** TVI, AHD, CVI kamere do 8MP@15fps na kanalima od 1 do 4<br>**Rezolucija snimanja IP kamera:** do 4K (8 IP kamera ili svih 24)<br>**Video kompresija:** H.265, H.264<br>**Video/audio ulazi:** 4ch BNC, 1ch audio<br>**Video/audio izlazi:** HDMI/VGA (FULL HD), CVBS (960x576), 1ch audio<br>**Ulazno/Izlazni saobraćaj:** 72/80 Mbps<br>**Smart funkcije:** Motion detection, video loss, audio detection<br>**Dodatni ulazi:** RJ45 mrežni ulaz, 2xUSB 2.0 interfejs, 1xRS485<br>**Mrežni protokoli:** TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE<br>**Hard disk prostor:** 2 sata HDD do 6TB kapaciteta<br>**Opšte:** Napajanje 12V DC, Potrošnja ≤12W bez HDD,<br>**Radna temperatura:** -10 ºC ~ +55 ºC<br>**Dimenzije:** 380mm ×315mm× 53mm (15" × 12.4"×2.1") | 306,00 | 255,00 |

# MREŽNI SNIMAČI - NVR (NETWORK VIDEO RECORDERS)- UNIVIEW

| NAZIV ARTIKLA | Kat. br. | Karakteristike | CENA EUR (gotovinski) | CENA EUR (racun bez PDV) |
|---|---|---|---|---|
| **NVR301-04S3** | 7283 | **NVR301-04S3**<br>**4-KANALNI MREŽNI SNIMAČ**<br>**Rezolucija snimanja:** 4K/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF<br>**Ulazno/Izlazni saobraćaj:** 64/48 Mbps<br>**Video kompresija:** Ultra 265, H.265, H.264 video kompresija,<br>**Video/audio izlazi:** 1-ch HDMI, 1-ch VGA, HDMI do 4K(3840x2160) rezolucije<br>**Smart funkcije:** Detekcija Lica, Intrusion detection, Cross line detection, Audio detection<br>**Pretraga snimka po smart funkcijama:** Face search, Behavior search<br>**ONVIF conformance:** Profile S, Profile G, Profile T<br>**Dodatni ulazi:** RJ45 mrežni ulaz, 2xUSB 2.0,.<br>**Mrežni protokoli:** P2P, UPnP, NTP, DHCP, PPPoE<br>**Hard disk prostor:** 1 sata HDD do 6TB kapaciteta<br>**Opšte:** Napajanje 48V DC, Potrošnja 5W bez HDD,<br>**Radna temperatura:** -10 ºC ~ +55 ºC,<br>**Dimenzije:** 260mm × 240mm × 46mm, Težina 1Kg | 108,00 | 90,00 |
| **NVR301-08S3** | 7284 | **NVR301-08S3**<br>**8-KANALNI MREŽNI SNIMAČ**<br>**Rezolucija snimanja:** 4K/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF<br>**Ulazno/Izlazni saobraćaj:** 64/48 Mbps<br>**Video kompresija:** Ultra 265, H.265, H.264 video kompresija,<br>**Video/audio izlazi:** 1-ch HDMI, 1-ch VGA, HDMI do 4K(3840x2160) rezolucije, 1x audio izlaz 3,5mm<br>**Smart Funkcije:** Detekcija Lica, Intrusion detection, Cross line detection, Audio detection<br>**Pretraga snimka po smart funkcijama:** Face search, Behavior search<br>**ONVIF conformance:** Profile S, Profile G, Profile T<br>**Dodatni ulazi:** RJ45 mrežni ulaz, 2xUSB 2.0,.<br>**Mrežni protokoli:** P2P, UPnP, NTP, DHCP, PPPoE<br>**Hard disk prostor:** 1 sata HDD do 6TB kapaciteta<br>**Opšte:** Napajanje 48V DC, Potrošnja 5W bez HDD,<br>**Radna temperatura:** -10 ºC ~ +55 ºC,<br>**Dimenzije:** 260mm × 240mm × 46mm, Težina 1Kg | 126,00 | 105,00 |
| **NVR501-08B** | 8582 | **NVR501-08B**<br>**Rezolucija snimanja**: 8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF<br>**Ulazno/Izlazni saobraćaj:** 80Mbps / 64Mbps<br>**Video kompresija**: Ultra 265/H.265/H.264<br>**Video/audio izlazi**: 1-ch HDMI, 1-ch VGA, HDMI do 4K(3840x2160) rezolucije, 1x RCA<br>**Smart Funkcije**: Detekcija upada, detekcija unakrsnih linija, ulazak u oblast, napuštanje oblasti, detekcija defokusiranja, otkrivanje promene scene, ostavljeni objekat, uklonjen objekat, automatsko praćenje, SMD (pametna detekcija pokreta).<br>**Pretraga snimka po smart funkcijama**: Pretraga ponašanja, izveštaj o brojanju ljudi.<br>**ONVIF conformance**: Profile S, Profile G, Profile T<br>**Dodatni ulazi**: 1 RJ-45 10M/100M self-adaptive Ethernet Interface, napred 1xUSB 2.0, nazad 1xUSB 3.0<br>**Mrežni protokoli**: TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE, HTTP, HTTPS, DNS, DDNS, SNMP, SMTP<br>**Hard disk prostor**: 1 sata HDD, do 8 TB.<br>**Opšte**: Napajanje - 52V DC/1.8A, Potrošnja ≤ 10W bez HDD.<br>**Radna temperatura**: -10°C~+ 55°C<br>**Dimenzije**: 260mm × 222mm × 47mm<br>**Težina**: ? 0.98Kg | 208,22 | 173,52 |
| **NVR302-16S2** | 7109 | **NVR302-16S2**<br>**16-KANALNI MREŽNI SNIMAČ**<br>**Rezolucija snimanja:** 8MP/ 6MP/ 5MP/ 4MP/ 3MP/ 1080p/ 960p/ 720p/ D1/ 2CIF/ CIF<br>**Ulazno/Izlazni saobraćaj:** 160/64 Mbps<br>**Video kompresija:** Ultra 265, H.265, H.264 video kompresija,<br>**Video/audio izlazi:** HDMI (4K) / HD, VGA<br>**Smart Funkcije:** Face detection, Intrusion detection, Cross line detection, Audio detection, Defocus detection, Scene change detection, Auto tracking, Object Left Behind, Object Removed, Face search, Behavior search<br>**Statisticke analize:** People counting<br>**ONVIF conformance:** Profile S, Profile G, Profile T<br>**Dodatni ulazi:** 2xRJ45 mrežni ulaz, 2xUSB 2.0, 1x USB 3.0<br>**Mrežni protokoli:** P2P, UPnP, NTP, DHCP, PPPoE<br>**Hard disk prostor:** 2 sata HDD do 6TB kapaciteta<br>**Opšte:** Napajanje 12V DC, Potrošnja 15W bez HDD,<br>**Radna temperatura:** -10 ºC ~ +55 ºC,<br>**Dimenzije:** 380mm × 315mm ×53mm, Težina 0,98Kg | 276,00 | 230,00 |

| | | | | |
|---|---|---|---|---|
| **NVR304-16X**<br> <br>Better Security, Better World. | 7289 | **NVR304-16X**<br>**16-KANALNI MREŽNI SNIMAČ**<br>**Rezolucija snimanja:** 12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF<br>**Ulazno/Izlazni saobraćaj:** 384/384 Mbps<br>**Video kompresija:** Ultra 265, H.265, H.264 video kompresija,<br>**Video/audio izlazi:** HDMI1 (4K) / VGA I HDMI2 nezavisni izlazi, 1ch RCA<br>**Smart Funkcije:** Face detection, Intrusion detection, Cross line detection, Audio detection, Defocus detection, Scene change detection, Auto tracking, Object left behind, Object removed, Face search, Behavior search<br>**Statisticke analize:** People counting<br>**ONVIF conformance:** Profile S, Profile G, Profile T<br>**Dodatni ulazi:** 2xRJ45 mrežni ulaz, 2xUSB 2.0, 1x USB 3.0, 1 x RS485, 1 x RS232, 16 x Alarmnih ulaza, 4 x Alarmnih izlaza<br>**Mrežni protokoli:** P2P, UPnP, NTP, DHCP, PPPoE<br>**Hard disk prostor:** 4 sata HDD do 10TB kapaciteta, RAID 1, 5<br>**Opšte:** Napajanje 12V DC, Potrošnja 25W bez HDD,<br>**Radna temperatura:** -10 ºC ~ +55 ºC,<br>**Dimenzije:** 442mm ×426mm× 89mm, Težina 5,7Kg | 660,00 | 550,00 |
| **NVR304-32X**<br> <br>Better Security, Better World. | 7111 | **NVR304-32X**<br>**32-KANALNI MREŽNI SNIMAČ**<br>**Rezolucija snimanja:** 12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF<br>**Ulazno/Izlazni saobraćaj:** 384/384 Mbps<br>**Video kompresija:** Ultra 265, H.265, H.264 video kompresija,<br>**Video/audio izlazi:** HDMI1 (4K) / VGA I HDMI2 nezavisni izlazi, 1ch RCA<br>**Smart Funkcije:** Face detection, Intrusion detection, Cross line detection, Audio detection, Defocus detection, Scene change detection, Auto tracking, Object left behind, Object removed, Face search, Behavior search<br>**Statisticke analize:** People counting<br>**ONVIF conformance:** Profile S, Profile G, Profile T<br>**Dodatni ulazi:** 2xRJ45 mrežni ulaz, 2xUSB 2.0, 1x USB 3.0, 1 x RS485, 1 x RS232, 16 x Alarmnih ulaza, 4 x Alarmnih izlaza<br>**Mrežni protokoli:** P2P, UPnP, NTP, DHCP, PPPoE<br>**Hard disk prostor:** 4 sata HDD do 10TB kapaciteta, RAID 1, 5<br>**Opšte:** Napajanje 12V DC, Potrošnja 25W bez HDD,<br>**Radna temperatura:** -10 ºC ~ +55 ºC,<br>**Dimenzije:** 442mm ×426mm× 89mm, Težina 5,7Kg | 768,00 | 640,00 |

# IP KAMERE 2 MPX UNIVIEW

| NAZIV ARTIKLA | Kat. br. | Karakteristike | CENA EUR (gotovinski) | CENA EUR (racun bez PDV) |
|---|---|---|---|---|
| **IPC2122LB-SF40-A**<br> <br>Better Security, Better World. | 7056 | **IPC2122LB-SF40-A**<br>**2 MP IR Fiksna Bullet Mrežna Kamera**<br>**Rezolucija snimanja:** 1080P (1920*1080), Max 30fps<br>**Čip:** 1/2.8", 2.0 megapixel, progressive scan, CMOS,<br>**Šater:** Auto/Manual, 1 ~ 1/100000s<br>**Optika:** 4.0mm@F2.0<br>**Osetljivost:** Colour: 0.01Lux (F2.0, AGC ON) 0Lux with IR on, IR-cut filter<br>**IC domet:** do 30m<br>**Interfejsi:** 10/100M Base-TX Ethernet<br>**Protokoli:** IPv4, IGMP, ICMP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, UPnP, HTTP<br>**Mrežni stadardi:** ONVIF (Profile S, Profile T), API<br>**Kompresija:** Ultra 265, H.265, H.264, MJPEG<br>**Smart funkcije:** **Motion detection**<br>**Ostale Karakteristike:** **2D/3D DNR, DWDR, HLC, BLC, OSD, Privacy mask, ROI.**<br>**Zaštita:** IP67<br>**Napajanje i potrošnja:** DC 12V±25%, PoE (IEEE 802.3af), max 5,5W<br>**Radna Temperatura:** -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)<br>**Dimenzije (DxŠxV):** 161 × 63 ×62mm  težina: 0,27kg<br><br>**Kompatibilni nosači i pribor:** TR-UP06-B-IN, TR-A01-IN, TR-UP06-C-IN, TR-JB05-A-IN | 75,00 | 62,50 |
| **IPC2122LB-SF28-A 2MP**<br> <br>Better Security, Better World. | 8031 | **IPC2122LB-SF28-A 2MP**<br>**2 MP IR Fiksna Bullet Mrežna Kamera**<br>**Rezolucija snimanja:** 1080P (1920*1080), Max 30fps<br>**Čip:** 1/2.8", 2.0 megapixel, progressive scan, CMOS,<br>**Šater:** Auto/Manual, 1 ~ 1/100000s<br>**Optika:** 2.8mm@F2.0<br>**Osetljivost:** Colour: 0.01Lux (F2.0, AGC ON) 0Lux with IR on, IR-cut filter<br>**IC domet:** do 30m<br>**Interfejsi:** 10/100M Base-TX Ethernet<br>**Protokoli:** IPv4, IGMP, ICMP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, UPnP, HTTP<br>**Mrežni standardi:** ONVIF (Profile S, Profile T), API<br>**Kompresija:** Ultra 265, H.265, H.264, MJPEG<br>**Smart funkcije:** Motion detection<br>**Ostale karakteristike:** 2D/3D DNR, DWDR, HLC, BLC, OSD, Privacy mask, ROI.<br>**Zaštita:** IP67<br>**Napajanje i potrošnja:** DC 12V±25%, PoE (IEEE 802.3af), max 5,5W<br>**Radna temperatura:** -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)<br>**Dimenzije (DxŠxV):** 161 × 63 ×62mm  težina: 0,27kg<br><br>**Kompatibilni nosači i pribor:** TR-UP06-B-IN, TR-A01-IN, TR-UP06-C-IN, TR-JB05-A-IN | 75,00 | 62,50 |
| **IPC2122LB-ADF28KM-G**<br> <br>Better Security, Better World. | 7505 | **IPC2122LB-ADF28KM-G**<br>**2 Mpx HD WDR Fiksna IR Bullet Mrežna Kamera**<br>**Rezolucija snimanja:** 1080P (1920*1080), Max 30fps<br>**Čip:** 1/2.7"", 2.0 megapixel, progressive scan, CMOS,<br>**Šater:** Auto/Manual, 1 ~ 1/100000s<br>**Optika:** 2.8mm@F2.0<br>**Osetljivost:** Colour: 0.01Lux (F2.0, AGC ON) 0Lux with IR on, IR-cut filter, 120db WDR<br>**IR domet:** do 30m<br>**Interfejsi:** 10/100M Base-TX Ethernet<br>**Protokoli:** IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL/TLS, SNMP<br>**Mrežni stadardi:** ONVIF (Profile S, Profile G, Profile T), API , SDK<br>**Kompresija:** Ultra 265, H.265, H.264, MJPEG<br>**Smart funkcije:**  **Motion detection, Tampering, Audio detection, Cross line, Intrusion**<br>**Ostale karakteristike:** **2D/3D DNR, HLC, BLC, Privacy mask, Flip, corridor mode 9:16, integrisan mikrofon, SD kartica do 128GB, ANR, NAS (NFS)**<br>**Zaštita:** IP67<br>**Napajanje i potrošnja:** DC 12V±25%, PoE (IEEE 802.3af), max 7W<br>**Radna temperatura:** -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)<br>**Dimenzije (DxŠxV):** 165 × 63 × 62mm  0,39kg<br><br>**Kompatibilni nosači i pribor:** TR-UP06-B-IN, TR-A01-IN, TR-UP06-C-IN, TR-JB05-A-IN" | 102,00 | 85,00 |

| | | | | |
|---|---|---|---|---|
| **IPC2122LB-ADF40KM-G**<br> <br><br>unv®<br>Better Security, Better World. | 7113 | **IPC2122LB-ADF40KM-G**<br>**2 MP HD WDR Fiksna Bullet Mrežna Kamera**<br>**Rezolucija snimanja:** 1080P (1920*1080) 30/25fps,<br>**Čip:** 1/2.7", 2.0 megapixel, progressive scan, CMOS,<br>**Šater:** Auto/Manual, 1 ~ 1/100000s<br>**Optika:** 4.0mm@F2.0<br>**Osetljivost:** Colour: 0.01Lux (F2.0, AGC ON) 0Lux with IR on, IR-cut filter, 120db WDR<br>**IC domet:** do 30m<br>**Interfejsi:** 10/100M Base-TX Ethernet<br>**Protokoli:** IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, QoS, SSL, SNMP<br>**Mrežni standardi:** ONVIF (Profile S, Profile T), API<br>**Kompresija:** Ultra 265, H.265, H.264, MJPEG<br>**Smart funkcije: Motion detection, Tampering, Audio detection, Cross line, Intrusion**<br>**Ostale Karakteristike: 2D/3D DNR, HLC, BLC, OSD, Privacy mask, ROI, Corridor mode 9:16, Integrisan mikrofon, Micro SD do 128 GB**<br>**Zaštita:** IP67<br>**Napajanje i potrošnja:** DC 12V±25%, PoE (IEEE 802.3af), max 7W<br>**Radna Temperatura:** -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)<br>**Dimenzije (DxŠxV):** 165 × 63 × 62mm, 0,39kg<br>**Kompatibilni nosači i pribor:** TR-UP06-B-IN, TR-A01-IN, TR-UP06-C-IN, TR-JB05-A-IN | 99,60 | 83,00 |
| **IPC2322LBR3-SPZ28-D**<br> <br><br>unv®<br>Better Security, Better World. | 5592 | **IPC2322LBR3-SPZ28-D**<br>**2 MP IR Varifokalna bullet Mrežna Kamera**<br>**Rezolucija snimanja:** 1080P (1920*1080), Max 30fps<br>**Čip:** 1/2.7", 2.0 megapixel, progressive scan, CMOS<br>**Šater:** Auto/Manual, 1 ~ 1/100000s<br>**Optika:** 2.8 ~ 12mm, motorizovani zoom<br>**Osetljivost:** 0.01Lux (F1.6, AGC ON) 0Lux with IR on, IR-cut filter<br>**IC domet:** do 30m<br>**Interfejsi:** 10/100M Base-TX Ethernet, MicroSD, do 256GB<br>**Protokoli:** IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP,<br>UPnP, HTTP, HTTPS, SMTP, SSL, QoS.<br>**Mrežni standardi:** ONVIF (Profile S, Profile T), API<br>**Kompresija:** Ultra 265, H.265, H.264, MJPEG<br>**Smart funkcije: Intrusion Detection, Motion detection, Tampering alarm.**<br>**Ostale Karakteristike: 2D/3D DNR, DWDR, HLC, BLC, OSD, Privacy mask, ROI.**<br>**Zaštita:** IP67<br>**Napajanje i potrošnja:** DC 12V±25%, PoE (IEEE 802.3af), max 6.5W<br>**Radna temperatura:** -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)<br>**Dimenzije (DxŠxV):** 240.3 × 86.4 × 75.6mm, težina: 1kg<br>**Kompatibilni nosači i pribor:** TR-UP06-B-IN, TR-A01-IN, TR-JB07-D-IN, TR-UP06-C-IN, TR -JB06-AIN | 150,00 | 125,00 |
| **IPC2322LB-ADZK-G**<br> <br><br>unv®<br>Better Security, Better World. | 7654 | **IPC2322LB-ADZK-G**<br>**2Mpx IR Varifokalna Bullet Mrežna kamera**<br><br>**Rezolucija snimanja:** 1080P (1920*1080) 30/25fps,<br>**Čip**: 1/2.7", 2.0 megapixel, progressive scan, CMOS<br>**Šater**: Auto/Manual, 1 ~ 1/100000s<br>**Optika**: 2.8 ~ 12mm, AF automatski fokus i motorizovani zoom<br>**Osetljivost**: Colour: 0.005Lux (F1.6, AGC ON), 0Lux with IR on,<br>**IC domet:** do 50m<br>**Interfejsi**: 10/100M Base-TX Ethernet, **Integrisan mikrofon**, Micro SD do 128GB, ANR, NAS (NFS)<br>**Protokoli**: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL/TLS, QoS, SNMP<br>**Mrežni standardi:** ONVIF (Profile S, Profile G, Profile T), API, SDK<br>**Kompresija:** Ultra 265, H.265, H.264, MJPEG<br>**Događaji**: **Motion detection, tampering alarm, audio detection**<br>**Smart funkcije: Cross line detection, Intrusion detection**<br>**Ostale karakteristike: 2D/3D DNR, HLC, BLC, Smart IR, Corridor mode 9:16, 120db WDR**<br>**Zaštita**: IP67<br>**Napajanje i potrošnja:** DC 12V±25%, PoE (IEEE 802.3af), max 8.5W<br>**Radna temperatura:** -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)<br>**Dimenzije (DxŠxV):** 206 × 74 × 74mm, 0,54kg<br>**Kompatibilni nosači i pribor:** TR-UP06-B-IN, TR-A01-IN, TR-UP06-C-IN, TR-JB05-A-IN | 180,00 | 150,00 |

| | | | | |
|---|---|---|---|---|
| **IPC2122SR3-UPF40-C**<br> <br><br>unv®<br>Better Security, Better World. | 6327 | **IPC2122SR3-UPF40-C**<br>**2 MP IR Fiksna Bullet Mrežna Kamera**<br>**Rezolucija snimanja:** 1080P (1920*1080), Max 30fps<br>**Čip:** 1/2.8", 2.0 megapixel, progressive scan, CMOS,<br>**Šater:** Auto/Manual, 1 ~ 1/100000s<br>**Optika:** 4.0mm@F1.6<br>**Osetljivost:** Colour: 0.001Lux (F1.6, AGC ON) 0Lux with IR on, IR-cut filter, **120db WDR**<br>**IC domet:** do 30m<br>**Interfejsi:** 10/100M Base-TX Ethernet<br>**Protokoli:** IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP,<br>UPnP, HTTP, HTTPS, SMTP, SSL, QoS.<br>**Mrežni standardi:** ONVIF (Profile S, Profile T), API<br>**Kompresija:** Ultra 265, H.265, H.264, MJPEG<br>**Smart funkcije:** **Intrusion Detection, Crossing line Detection, Motion detection,Tampering alarm, Scene Change Detection, Defocus Detection, People Counting, Face Detection.**<br>**Ostale Karakteristike:** **2D/3D DNR, HLC, BLC, OSD, Privacy mask, ROI.**<br>**Zaštita:** IP67<br>**Napajanje i potrošnja:** DC 12V±25%, PoE (IEEE 802.3af), max 6W<br>**Radna Temperatura:** -35°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)<br>**Dimenzije (DxŠxV):** 157.3 × 62.4 × 63mm, 0,45kg<br>**Kompatibilni nosači i pribor:** TR-UP06-B-IN, TR-A01-IN, TR-UP06-C-IN, TR-JB05-A-IN | 132,00 | 110,00 |
| **IPC2222EBR5-HDUPF40**<br> <br><br>unv®<br>Better Security, Better World. | 6337 | **IPC2222EBR5-HDUPF40**<br>**2 MP IR Fiksna Bullet Mrežna Kamera**<br>**Rezolucija snimanja:** 1080P (1920*1080), Max 60fps<br>**Čip:** 1/2.8", 2.0 megapixel, progressive scan, CMOS<br>**Šater:** Auto/Manual, 1 ~ 1/100000s<br>**Optika:** 4.0mm@F1.6<br>**Osetljivost:** Colour: 0.001Lux (F1.6, AGC ON) 0Lux with IR on WDR: 120db<br>**IC domet:** do 50m<br>**Interfejsi:** 10/100M Base-TX Ethernet, Micro SD slot do 256GB<br>**Protokoli:** IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS.<br>**Mrežni standardi:** ONVIF (Profile S, Profile T), API<br>**Kompresija:** Ultra 265, H.265, H.264, MJPEG<br>**Smart funkcije:** **Intrusion Detection, Cross line, Object left behind and object removed detection, Motion detection, Tampering alarm, Scene Change Detection, Defocus Detection, People counting, Face detection.**<br>**Ostale Karakteristike:** **Digital Defog, 2D/3D DNR, HLC, BLC, OSD, Privacy mask, ROI, Corridor mod**<br>**Zaštita:** IP67<br>**Napajanje i potrošnja:** DC 12V±25%, PoE (IEEE 802.3af), max 7.5W<br>**Radna Temperatura:** -35°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)<br>**Dimenzije (ΦxV):** 253.4 × 86 × 71.7mm (9.98” × 3.4” × 2.8”)<br><br>**Kompatibilni nosači i pribor:** TR-UP06-B-IN, TR-A01-IN, TR-JB07-D-IN, TR-JB06-A-IN, TR-UP06-C-IN | 163,20 | 136,00 |
| **IPC2222ER5-DUPF40-C**<br> <br><br>unv®<br>Better Security, Better World. | 6333 | **IPC2222ER5-DUPF40-C**<br>**2 MP IR Fiksna Bullet Mrežna Kamera**<br>**Rezolucija snimanja:** 1080P (1920*1080), Max 30fps<br>**Čip:** 1/2.8", 2.0 megapixel, progressive scan, CMOS<br>**Šater:** Auto/Manual, 1 ~ 1/100000s<br>**Optika:** 4.0mm@F1.2<br>**Osetljivost:** Colour: 0.0005Lux (F1.2, AGC ON) 0Lux with IR on **WDR: 120db**<br>**IC domet:** do 50m<br>**Interfejsi:** 10/100M Base-TX Ethernet, Micro SD slot do 256GB<br>**Protokoli:** IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS.<br>**Mrežni standardi:** ONVIF (Profile S, Profile T), API<br>**Kompresija:** Ultra 265, H.265, H.264, MJPEG<br>**Smart funkcije:** **Intrusion Detection, Cross line, Object left behind and object removed detection, Motion detection, Tampering alarm, Scene Change Detection, Defocus Detection, People counting, Face detection.**<br>**Ostale Karakteristike:** **Digital Defog, 2D/3D DNR, HLC, BLC, OSD, Privacy mask, ROI, Corridor mod**<br>**Zaštita:** IP67<br>**Napajanje i potrošnja:** DC 12V±25%, PoE (IEEE 802.3af), max 9W<br>**Radna Temperatura:** -35°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)<br>**Dimenzije (ΦxV):** 253.4 × 86 × 71.7mm (9.98” × 3.4” × 2.8”)<br>**Kompatibilni nosači i pribor:** TR-UP06-B-IN, TR-A01-IN, TR-JB07-D-IN, TR-JB06-A-IN, TR-UP06-C-IN | 159,00 | 132,50 |

| | | | | |
|---|---|---|---|---|
| **IPC2312SB-ADF40KM-I0**<br> <br> | 7650 | **IPC2312SB-ADF40KM-I0**<br>**2Mpx IR Fiksna Bullet Mrežna kamera**<br><br>**Rezolucija snimanja:** 1080P (1920*1080) 30/25fps,<br>**Čip:** 1/2.8", 2.0 megapixel, progressive scan, CMOS<br>**Šater:** Auto/Manual, 1 ~ 1/100000s<br>**Optika:** 4.0mm@F1.6<br>**Osetljivost:** Colour: 0.001Lux (F1.6, AGC ON), 0Lux with IR on, 120db WDR<br>**IC domet:** do 80m<br>**Interfejsi:** 10/100M Base-TX Ethernet, Alarmni ulaz/izlaz 1/1, **Integrisana 2 mikrofona**, Micro SD do 256 GB, ANR, NAS (NFS)<br>**Protokoli:** IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, RTMP,SSL/TLS, SSH<br>**Mrežni standardi:** ONVIF (Profile S, Profile G, Profile T), API, SDK<br>**Kompresija:** Ultra 265, H.265, H.264, MJPEG<br>**Događaji: Motion detection, tampering alarm, audio detection, alarm input/output**<br>**Smart funkcije: Smart intrusion prevention (filtriranje ljudi i vozila radi smanjenja lažnih alarma) - Cross Line detection, Intrusion detection, Enter Area detection, Leave Area detection, Face detection, people flow counting, crowd density monitoring**<br>**Ostale Karakteristike: 2D/3D DNR, HLC, BLC, Smart IR, Corridor mode 9:16**<br>**Zaštita**: IP67<br>**Napajanje i potrošnja:** DC 12V±25%, PoE (IEEE 802.3af), max 7W<br>**Radna Temperatura:** -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)<br>**Dimenzije (DxŠxV):** 206 × 74 × 74mm, 0,51kg<br>**Kompatibilni nosači i pribor:** TR-UP06-B-IN, TR-A01-IN, TR-UP06-C-IN, TR-JB05-A-IN | 200,40 | 167,00 |
| **IPC322LB-SF28-A**<br> <br> | 7059 | **IPC322LB-SF28-A**<br>**2 MP IR Fiksna Dome Mrežna Kamera**<br>**Rezolucija snimanja:** 1080P (1920*1080), Max 30fps<br>**Čip:** 1/2.8", 2.0 megapixel, progressive scan, CMOS,<br>**Šater:** Auto/Manual, 1 ~ 1/100000s<br>**Optika:** 2.8mm@F2.0<br>**Osetljivost:** Colour: 0.01Lux (F2.0, AGC ON) 0Lux with IR on, IR-cut filter<br>**IC domet:** do 30m<br>**Interfejsi:** 10/100M Base-TX Ethernet<br>**Protokoli:** IPv4, IGMP, ICMP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, UPnP, HTTP<br>**Mrežni standardi:** ONVIF (Profile S, Profile T), API<br>**Kompresija:** Ultra 265, H.265, H.264, MJPEG<br>**Smart funkcije: Motion detection**<br>**Ostale Karakteristike: 2D/3D DNR, true WDR 120dB, HLC, BLC, OSD, Privacy mask, ROI.**<br>**Zaštita:** IP67, IK10<br>**Napajanje i potrošnja:** DC 12V±25%, PoE (IEEE 802.3af), max 5W<br>**Radna Temperatura:** -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)<br>**Dimenzije:** Φ109 x 81mm, težina: 0,35kg<br>**Kompatibilni nosači i pribor:** TR-JB03-G-IN, TR-JB07/WM03-G-IN, TR-WM03-D-IN, TR-UM06-E-IN,<br>TR-UP06-IN, TR-A01-IN, TR-SE24-IN, TR-SE24-A-IN, TR-CM24-IN | 89,10 | 74,25 |
| **IPC322LB-DSF28K-G**<br> <br> | 7581 | **IPC322LB-DSF28K-G**<br>**2Mpx IR Fiksna Dome Mrežna kamera**<br><br>**Rezolucija snimanja:** 1080P (1920*1080) 30fps<br>**Čip:** 1/2.7", 2.0 megapixel, progressive scan, CMOS<br>**Šater:** Auto/Manual, 1 ~ 1/100000s<br>**Optika:** 2.8mm @2.0<br>**Osetljivost:** Colour: 0.01Lux ( F2.0, AGC ON), 0 Lux with IR<br>**IC domet:** do 30m<br>**Interfejsi:** 10/100M Base-TX Ethernet, Micro SD do 128GB, ANR, NAS (NFS)<br>**Protokoli:** IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL/TLS, SNMP<br>**Mrežni standardi:** ONVIF (Profile S, Profile G, Profile T), API, SDK<br>**Kompresija:** Ultra 265, H.265, H.264, MJPEG<br>**Događaji: Motion detection, Audio detection, Tampering alarm**<br>**Smart funkcije: Cross line detection, Intrusion detection**<br>**Ostale karakteristike: 2D/3D DNR, HLC, BLC, Smart IR, Corridor mode 9:16, 120db WDR**<br>**Zaštita:** IP67, IK10<br>**Napajanje i potrošnja:** DC 12V±25%, PoE (IEEE 802.3af), max 5W<br>**Radna temperatura:** -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)<br>**Dimenzije (DxŠxV):** Φ109 x 81mm, 0,36 kg<br>**Kompatibilni nosači i pribor:** TR-JB03-G-IN, TR-JB07/WM03-G-IN, TR-WM03-D-IN, TR-A01-IN, TR-UP06-IN, TR-UM06-E-IN, TR-SE24-IN, TR-SE24-A-IN, TR-CM24-IN | 108,00 | 90,00 |

| | | | | |
|---|---|---|---|---|
| **IPC3612LB-ADF28K-G 2MP Kamera**<br> <br><br>unv® Better Security, Better World. | 8513 | **IPC3612LB-ADF28K-G 2MP Kamera**<br>**2 MP HD WDR Fiksna Turret Mrežna Kamera**<br>**Rezolucija snimanja**: 1080P (1920*1080) 30 fps max.<br>**Čip**: 1/2.7″, 2 MP, progressive scan, CMOS.<br>**Šater**: Auto/Manual, 1 ~ 1/100000s.<br>**Optika**: 2.8mm @F2.0.<br>**Osetljivost**: Colour: 0.01 lux ( F2.0, AGC ON) 0 lux with IR.<br>**IC domet**: do 30m.<br>**Interfejsi**: 10/100M Base-TX Ethernet. MicroSD do 128 GB, ugrađen mikrofon.<br>**Protokoli**: IPv4, IGMP, ICMP,ARP, TCP, UDP, DHCP,RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS.<br>**Mrežni standardi**: ONVIF (Profile S, Profile T),API.<br>**Kompresija**: Ultra 265, H.265, H.264, MJPEG<br>**Smart funkcije**: **Motion detection, Tampering, Audio detection, Human body detection.**<br>**Ostale karakteristike**: **2D/3D DNR, WDR 120dB, HLC, BLC, OSD, Privacy mask, ROI.**<br>**Zaštita**: IP67<br>**Napajanje i potrošnja**: DC 12V ~ 25%, PoE (IEE 802.3 af), max 7 W.<br>**Radna temperatura**: -30°C ~ 60°C<br>**Dimenzije** (DxŠxV): Φ118 x 96mm<br>**Težina**: 0.3 kg.<br>**Kompatibilni nosači i pribor**: TR-JB03-I-IN, TR-JB07/WM03-G-IN, TR-WM03-D-IN, TR-UP06-IN, TR-A01-IN, TR-SE24-IN, TR-SE24-A-IN, TR-CM24-IN | 122,53 | 102,11 |
| **IPC322SB-DF28K-I0**<br> <br><br>unv® Better Security, Better World. | 7291 | **IPC322SB-DF28K-I0**<br>**2 MP Lighthunter Fiksna Anti Vandal Dome Mrežna Kamera**<br>**Rezolucija snimanja:** 2MP (1920*1080)@30/25fps<br>**Čip:** 1/2.8", 2.0 megapixel, progressive scan, CMOS<br>**Šater:** Auto/Manual, 1 ~ 1/100000s<br>**Optika:** 2.8mm @F1.6<br>**Osetljivost:** Colour: 0.001Lux (F1.6, AGC ON)0Lux sa IR, IR-cut filter, WDR:120db, IC domet do 30m<br>**Interfejsi:** 10/100M Base-TX Ethernet, Micro SD slot do 256GB, **1x Alarmni ulaz/izlaz, 1x Audio ulaz/izlaz**<br>**Protokoli:** IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS<br>**Mrežni standardi:** ONVIF (Profile S, Profile T), API<br>**Kompresija:** Ultra 265, H.265, H.264, MJPEG<br>**Smart funkcije: Motion detection, tampering alarm, audio detection, Cross Line, Intrusion, Enter Area, Leave Area detection, Smart intrusion prevention**<br>**Ostale Karakteristike: 2D/3D DNR, HLC, BLC, OSD, Privacy mask, ROI, Corridor mode 9:16**<br>**Zaštita:** IP67, IK10<br>**Napajanje i potrošnja:** DC 12V±25%, PoE (IEEE 802.3af), max 5W<br>**Radna temperatura:** -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)<br>**Dimenzije (ΦxV):** Φ108.7 x 81.1mm težina: 0,42kg<br>**Kompatibilni nosači i pribor:** TR-UM06-E-IN, TR-UP06-IN, TR-A01-IN, TR-JB03-G-IN, TR-JB07/WM03-G-IN, TR-WM03-D-IN, TR-SE24-IN, TR-SE24-A-IN, TR-CM24-IN | 168,00 | 140,00 |
| **IPC3232LR3-VSPZ28-D**<br> <br><br>unv® Better Security, Better World. | 5851 | **IPC3232LR3-VSPZ28-D**<br>**2 MP IR Varifokalna Dome Mrežna Kamera**<br>**Rezolucija snimanja**: : 1080P (1920*1080), Max 30fps<br>**Čip:** 1/2.7", 2.0 megapixel, progressive scan, CMOS<br>**Šater:** Auto/Manual, 1 ~ 1/100000s<br>**Optika**: 2.8mm @F2.0<br>**Osetljivost**: 0.02Lux ( F2.0, AGC ON) 0Lux with IR on, IR-cut filter<br>**IC domet:** do 30m<br>**Interfejsi**: 10/100M Base-TX Ethernet<br>**Protokoli**: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP,<br>UPnP, HTTP, HTTPS, SMTP, SSL, QoS.<br>**Mrežni standardi**: ONVIF (Profile S, Profile T), API<br>**Kompresija**: Ultra 265, H.265, H.264, MJPEG<br>**Smart funkcije: Motion detection**<br>**Ostale Karakteristike: Digital defog, 2D/3D DNR, DWDR, HLC, BLC, OSD, Privacy mask, ROI.**<br>**Zaštita**: IP67, IK10<br>**Napajanje i potrošnja**: DC 12V±25%, PoE (IEEE 802.3af), max 4W<br>**Radna Temperatura**: -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)<br>**Dimenzije (ΦxV)**: Φ109 x 81mm težina: 0,35kg<br>**Kompatibilni nosači i pribor:** TR-JB04-C-IN, TR-JB07/WM04-B-IN, TR-WM04-IN, TR-FM152-A-IN, TR-UP06-IN, TR-A01-IN, TR-SM04-IN, TR-SE24-IN, TR-SE24-A-IN, TR-CM24-IN | 156,00 | 130,00 |

# IP KAMERE 4 MPX UNIVIEW

| NAZIV ARTIKLA | Kat. br. | Karakteristike | CENA EUR (gotovinski) | CENA EUR (racun bez PDV) |
|---|---|---|---|---|
| **IPC2124LE-ADF40KM-G**<br> <br>Better Security, Better World. | 7060 | **IPC2124LE-ADF40KM-G**<br>**4 MP Mini IR Fiksna Bullet Mrežna Kamera**<br>**Rezolucija snimanja:** 4MP (2688*1520)@ 30/25fps<br>**Čip:** 1/3", 4.0 megapixel, progressive scan, CMOS<br>**Šater:** Auto/Manual, 1 ~ 1/100000s<br>**Optika:** 4.0mm@F1.6<br>**Osetljivost:** Colour: 0.003Lux (F1.6, AGC ON) 0Lux with IR on, IR-cut filter<br>**IC domet**: do 50m<br>**Interfejsi:** 10/100M Base-TX Ethernet, Micro SD do 256GB<br>**Protokoli:** IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, 802.1x, SNMP<br>**Mrežni standardi:** ONVIF (Profile S, Profile T), API<br>**Kompresija:** Ultra 265, H.265, H.264, MJPEG<br>**Smart funkcije: Motion detection, Tampering detection, Audio detection, Cross line, Intrusion detection**<br>**Ostale Karakteristike: 2D/3D DNR, true WDR 120dB, HLC, BLC, OSD, Privacy mask, ROI, Integrisan mikrofon, Corridor mode 9:16**<br>**Zaštita:** IP67<br>**Napajanje i potrošnja:** DC 12V±25%, PoE (IEEE 802.3af), max 6W<br>**Radna Temperatura:** -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)<br>**Dimenzije (DxŠxV):** 190×73×71mm težina: 0,45kg<br>**Kompatibilni nosači i pribor:** TR-JB06-IN, TR-A01-IN, TR-UP06-C-IN, TR-JB05-A-IN | 147,60 | 123,00 |
| **IPC2124LE-ADF28KM-G**<br> <br>Better Security, Better World. | 7178 | **IPC2124LE-ADF28KM-G**<br>**4 MP Mini IR Fiksna Bullet Mrežna Kamera**<br><br>**Rezolucija snimanja:** 4MP (2688*1520)@ 30/25fps<br>**Čip:** 1/3", 4.0 megapixel, progressive scan, CMOS<br>**Šater:** Auto/Manual, 1 ~ 1/100000s<br>**Optika:** 2.8mm@F1.6<br>**Osetljivost:** Colour: 0.003Lux (F1.6, AGC ON) 0Lux with IR on, IR-cut filter<br>**IC domet:** do 50m<br>**Interfejsi:** 10/100M Base-TX Ethernet, Micro SD do 256GB<br>**Protokoli:** IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, 802.1x, SNMP<br>**Mrežni standardi:** ONVIF (Profile S, Profile T), API<br>**Kompresija:** Ultra 265, H.265, H.264, MJPEG<br>**Smart funkcije: Motion detection, Tampering detection, Audio detection, Cross line, Intrusion detection**<br>**Ostale Karakteristike: 2D/3D DNR, true WDR 120dB, HLC, BLC, OSD, Privacy mask, ROI., Integrisan mikrofon, Corridor mode 9:16**<br>**Zaštita:** IP67<br>**Napajanje i potrošnja:** DC 12V±25%, PoE (IEEE 802.3af), max 6W<br>**Radna Temperatura:** -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)<br>**Dimenzije (DxŠxV):** 190×73×71mm težina: 0,45kg<br>**Kompatibilni nosači i pribor:** TR-JB06-IN, TR-A01-IN, TR-UP06-C-IN, TR-JB05-B-IN | 147,60 | 123,00 |
| **IPC324LE-DSF28K-G**<br> <br>Better Security, Better World. | 7055 | **IPC324LE-DSF28K-G**<br>**4 MP IR AntiVandal Fiksna Dome Mrežna Kamera**<br>**Rezolucija snimanja:** 4MP (2688*1520), Max 30fps<br>**Čip:** 1/3", 4.0 megapixel, progressive scan, CMOS<br>**Šater:** Auto/Manual, 1 ~ 1/100000s<br>**Osetljivost:** 0.0003Lux (F1.6, AGC ON) 0Lux with IR on, IR-cut filter<br>**IC domet:** do 30m<br>**Interfejsi:** 10/100M Base-TX Ethernet, MicroSD, do 256GB<br>**Protokoli:** IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, 802.1x, SNMP<br>**Mrežni standardi:** ONVIF (Profile S, Profile T), API<br>**Kompresija:** Ultra 265, H.265, H.264, MJPEG<br>**Smart funkcije: Motion detection, Tampering alarm, Cross line, Intrusion detection**<br>**Ostale karakteristike: Digital Defog, 2D/3D DNR, true WDR 120dB, HLC, BLC, OSD, Privacy mask, ROI, Corridor mod 9:16**<br>**Zaštita:** IP67, IK10<br>**Napajanje i potrošnja:** DC 12V±25%, PoE (IEEE 802.3af), max 5,5W<br>**Radna Temperatura:** -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)<br>**Dimenzije (ΦxV):** Φ109 x 81mm ,  težina: 0.35kg<br><br>**Kompatibilni nosači i pribor:** TR-UM06-E-IN, TR-UP06-IN, TR-A01-IN, TR-JB03-G-IN, TR-JB0T/WM03-G-IN, TR-WM03-D-IN, TR-SE24-IN, TR-SE24-A-IN, TR-CM24-IN | 147,60 | 123,00 |

| | | | | |
|---|---|---|---|---|
| **IPC2224SS-DF40K**<br> <br>Better Security, Better World. | 6715 | **IPC2224SS-DF40K**<br>**4 MP Lighthunter Deep learning Bullet Mrežna Kamera sa WDR-om**<br>**Rezolucija snimanja:** 4MP (2592*1520), Max 30fps<br>**Čip**: 1/1,8", 4.0 megapixel, progressive scan, CMOS<br>**Šater:** Auto/Manual, 1 ~ 1/100000s<br>**Optika:** 4.0mm @F1.6<br>**Osetljivost:** 0.001Lux (F1.6, AGC ON) 0Lux with IR on, IR-cut filter, WDR: 120db<br>**IC domet:** do 50m<br>**Interfejsi:** 10/100M Base-TX Ethernet, MicroSD, do 256GB<br>**Protokoli:** IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS.<br>**Mrežni standardi:** ONVIF (Profile S, Profile T), API<br>**Kompresija:** Ultra 265, H.265, H.264, MJPEG<br>**Smart funkcije: Motion detection, tampering, audio loss detection, cross line, intrusion, object removed, object left behind, defocus, scene change, human body detection**<br>**Ostale Karakteristike: 2D/3D DNR, HLC, BLC, OSD, Privacy mask, ROI.**<br>**Zaštita:** IP67, IK10<br>**Napajanje i potrošnja:** DC 12V±25%, PoE (IEEE 802.3af), max 9W<br>**Radna temperatura:** -40°C ~ 60°C (-40°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)<br>**Dimenzije (DxŠxV):** 245.6x85.7x85.4mm, težina: 0,90kg<br>**Kompatibilni nosači i pribor:** TR-UP06-B-IN, TR-A01-IN, TR-JB07-D-IN, TR-UP06-C-IN, R-JB06-A-IN | 174,00 | 145,00 |
| **IPC2324LBR3-SPZ28-D**<br> <br>Better Security, Better World. | 5865 | **IPC2324LBR3-SPZ28-D**<br>**4 MP IR Varifokalna Bullet Mrežna Kamera**<br>**Rezolucija snimanja: :** 4MP (2592*1520), Max 20fps;<br>**Čip:** 1/3", 4.0 megapixel, progressive scan, CMOS<br>**Šater:** Auto/Manual, 1 ~ 1/100000s<br>**Optika:** 2.8 ~ 12mm, motorizovani zoom<br>**Osetljivost:** 0.01Lux (F1.6, AGC ON) 0Lux with IR on, IR-cut filter<br>**IC domet:** do 30m<br>**Interfejsi:** 10/100M Base-TX Ethernet, MicroSD, do 256GB<br>**Protokoli:** IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS.<br>**Mrežni standardi:** ONVIF (Profile S, Profile T), API<br>**Kompresija:** Ultra 265, H.265, H.264, MJPEG<br>**Smart funkcije: Intrusion Detection, Motion detection,Tampering alarm.**<br>**Ostale Karakteristike: 2D/3D DNR, DWDR, HLC, BLC, OSD, Privacy mask, ROI.**<br>**Zaštita:** IP67<br>**Napajanje i potrošnja:** DC 12V±25%, PoE (IEEE 802.3af), max 6.5W<br>**Radna Temperatura:** -40°C ~ 60°C (-40°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)<br>**Dimenzije (DxŠxV):** 240.3 × 86.4 × 75.6mm, težina: 1kg<br>**Kompatibilni nosači i pribor:** TR-UP06-B-IN, TR-A01-IN, TR-JB07-D-IN, TR-UP06-C-IN, TR-JB06-A-IN | 156,00 | 130,00 |
| **IPC2324LB-ADZK-G**<br> <br>Better Security, Better World. | 7181 | **IPC2324LB-ADZK-G**<br>**4 MP HD IR Bullet Mrežna Kamera**<br>**Rezolucija snimanja:** 4MP (2688*1520)@ 25/20fps; 4MP (2560*1440)@ 25/20fps<br>**Čip:** 1/3", 4.0 megapixel, progressive scan, CMOS<br>**Šater:** Auto/Manual, 1 ~ 1/100000s<br>**Optika:** 2.8 ~ 12mm, AF automatsko fokusiranje i motorizovan zoom<br>**Osetljivost:** Color: 0.003Lux (F1.6, AGC ON) 0Lux with IR on, IR-cut filter<br>**IC domet:** do 50m<br>**Interfejsi:** 10/100M Base-TX Ethernet, Micro SD kartica do 256 GB, integrisan mikrofon<br>**Protokoli:** IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS, 802.1x, SNMP<br>**Mrežni standardi:** ONVIF (Profile S, Profile T), API<br>**Kompresija:** Ultra 265, H.265, H.264, MJPEG<br>**Smart funkcije: Motion detection,Tampering alarm, Audio detection, Cross line, Intrusion (bazirano na human body detection)**<br>**Ostale Karakteristike: 2D/3D DNR, true WDR 120dB, HLC, BLC, OSD, Privacy mask, ROI, Corridor mode 9:16**<br>**Zaštita:** IP67<br>**Napajanje i potrošnja:** DC 12V±25%, PoE (IEEE 802.3af), max 8.5W<br>**Radna temperatura:** -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)<br>**Dimenzije (DxŠxV):** 206 × 74 × 74mm težina: 0,55kg<br><br>**Kompatibilni nosači i pribor:** TR-JB06-IN, TR-A01-IN, TR-UP06-C-IN, TR-JB05-B-IN | 186,00 | 155,00 |

| | | | | |
|---|---|---|---|---|
| **IPC3614LE-ADF28K**<br> <br> | 7503 | **IPC3614LE-ADF28K**<br>**4Mpx Fiksna EasyStar Turret Mrežna Kamera**<br>**Rezolucija snimanja:** 4MP (2688*1520), Max 25fps<br>**Čip:** 1/3"", 4.0 megapixel, progressive scan, CMOS<br>**Šater:** Auto/Manual, 1 ~ 1/100000s<br>**Optika:** 2.8mm @F1.6<br>**Osetljivost:** 0.005Lux (F 1.6, AGC ON) 0Lux with IR on, IR-cut filter, WDR: 120db<br>**IR domet:** do 30m<br>**Interfejsi:** 10/100M Base-TX Ethernet<br>**Protokoli:** IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL<br>**Mrežni standardi:** ONVIF (Profile S, Profile G, Profile T), API<br>**Kompresija:** Ultra 265, H.265, H.264, MJPEG<br>**Smart funkcije: motion detection, tampering alarm, audio detection, human body detection**<br>**Ostale karakteristike: 2D/3D DNR, HLC, BLC, OSD, Privacy mask, Flip, SD kartica do 256GB, ANR**<br>**Zaštita:** IP67<br>**Napajanje i potrošnja:** DC 12V±25%, PoE (IEEE 802.3af), max 3W<br>**Radna temperatura:** -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)<br>**Dimenzije (ΦxV):** Φ118 x 96mm, težina: 0.35kg<br><br>**Kompatibilni nosači i pribor:** TR-JB03-I-IN, TR-JB07/WM03-G-IN, TR-WM03-D-IN, TR-UP06-IN, TR-A01-IN, TR-SE24-IN, TR-SE24-A-IN, TR-CM24-IN | 148,20 | 123,50 |
| **IPC3234LR3-VSPZ28-D**<br> <br> | 5595 | **IPC3234LR3-VSPZ28-D**<br>**4 MP IR Varifokalna Dome Mrežna Kamera**<br>**Rezolucija snimanja:** 4MP (2592*1520), Max 20fps;<br>**Čip:** 1/3", 4.0 megapixel, progressive scan, CMOS<br>**Šater:** Auto/Manual, 1 ~ 1/100000s<br>**Optika:** 2.8 ~ 12mm, motorizovani zoom<br>**Osetljivost:** 0.01Lux (F1.6, AGC ON) 0Lux with IR on, IR-cut filter<br>**IC domet:** do 30m<br>**Interfejsi:** 10/100M Base-TX Ethernet, MicroSD, do 256GB<br>**Protokoli:** IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS.<br>**Mrežni standardi:** ONVIF (Profile S, Profile T), API<br>**Kompresija:** Ultra 265, H.265, H.264, MJPEG<br>**Smart funkcije: Intrusion Detection, Motion detection,Tampering alarm.**<br>**Ostale karakteristike: Digital Defog, 2D/3D DNR, DWDR, HLC, BLC, OSD, Privacy mask, ROI.**<br>**Zaštita:** IP67, IK10<br>**Napajanje i potrošnja:** DC 12V±25%, PoE (IEEE 802.3af), max 6W<br>**Radna temperatura:** -40°C ~ 60°C (-40°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)<br>**Dimenzije (ΦxV):** Φ148 x 111.3mm, težina: 0.92kg<br><br>**Kompatibilni nosači i pribor:** TR-FM152-A-IN, TR-WM04-IN, TR-UP06-IN, TR-SM04-IN, TR-A01-IN, TR-JB04-C-IN, TR-JB07/WM04-B-IN, TR-SE24-IN, TR-SE24-A-IN, TR-CM24-IN | 168,00 | 140,00 |
| **IPC2K24SE-ADF40KMC-WL-I0**<br> <br> | 8035 | **IPC2K24SE-ADF40KMC-WL-I0**<br>**4 MP ColorHunter Širokougaona Fiksna Mrežna Kamera, sa tehnologijom dvostrukog soča omogućava ugao vidljivosti od 160°, dok Colorhunter tehnologija pruža 24/7 slike u boji.**<br>**Rezolucija snimanja:** 4MP (3840*1080)@25fps<br>**Čip:** 1/2.9", 4.0 megapixel, progressive scan, CMOS<br>**Šater:** Auto/Manual, 1 ~ 1/100000s<br>**Optika:** 2 * 4.0mm@F1.0<br>**Osetljivost:** Colour: 0.0005 lux (F1.0, AGC ON) DWDR<br>**LED domet:** do 30m, 2 LED-a<br>**Interfejsi:** 10/100M Base-TX Ethernet, MicroSD do 256GB, ANR, NAS (NFS) Audio ulaz/izlaz 1/1, Alarmni ulaz/izlaz 1/1, **Integrisana 2 mikrofona i 1 zvučnik**<br>**Protokoli:** IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, RTMP,SSL/TLS, SSH<br>**Mrežni stadardi:** ONVIF (Profile S, Profile G, Profile T), API,SDK<br>**Kompresija:** Ultra 265, H.265, H.264, MJPEG<br>**Smart funkcije: Human body detection, motion detection, tampering alarm, audio detection**<br>**Ostale karakteristike:** 2D/3D DNR, HLC, BLC, OSD, Privacy mask, ROI.<br>**Zaštita:** IP67, IK10<br>**Napajanje i potrošnja:** DC 12V±25%, PoE (IEEE 802.3af), max 6.5W<br>**Radna temperatura:** 30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)<br>**Dimenzije (DxŠxV):** 273× 130 × 76mm, težina: 0,95kg<br><br>**Kompatibilni nosači i pribor:** TR-UP06-B-IN, TR-A01-IN, TR-JB07-D-IN, TR-JB06-A-IN, TR-UP06-C-IN | 420,00 | 350,00 |

# IP KAMERE 5 MPX UNIVIEW

| NAZIV ARTIKLA | Kat. br. | Karakteristike | CENA EUR (gotovinski) | CENA EUR (racun bez PDV) |
|---|---|---|---|---|
| **IPC325ER3-DUVPF28**<br> <br><br>unv®<br>Better Security, Better World. | 5857 | **IPC325ER3-DUVPF28**<br>**5 MP IR Fiksna Dome Mrežna Kamera sa WDR-om**<br><br>**Rezolucija snimanja:** 5MP (2592*1944), Max 20fps; 5MP (2592*1944), Max 25fps (WDR OFF)<br>**Čip:** 1/2.7", 5.0 megapixel, progressive scan, CMOS<br>**Šater:** Auto/Manual, 1 ~ 1/100000s<br>**Optika:** 2.8mm @F1.6<br>**Osetljivost:** 0.005Lux (F1.6, AGC ON) 0Lux with IR on, IR-cut filter,**WDR: 120db**<br>**IC domet:** do 30m<br>**Interfejsi:** 10/100M Base-TX Ethernet, MicroSD, do 256GB, 2x Audio ulaz, 1x Audio izlaz, 1x Alarm ulaz, 1x Alarmni izlaz<br>**Protokoli: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS**<br>**Mrežni standardi:** ONVIF (Profile S, Profile T), API<br>**Kompresija:** Ultra 265, H.265, H.264, MJPEG<br>**Smart funkcije: Intrusion Detection, Motion detection,Tampering alarm, Line Crossing, Face detection, Audio Detection.**<br>**Inteligentne indentifikacije: Defocus, Promena scene, Ostavljeni objekat, Pomereni objekat.,**<br>**Statističke analize:** Brojanje Ljudi<br>**Ostale Karakteristike: 2D/3D DNR, HLC, BLC, OSD, Privacy mask, ROI, 9:16 Corridor mod**<br>**Zaštita:** IP67, IK10<br>**Napajanje i potrošnja:** DC 12V±25%, PoE (IEEE 802.3af), max 5W<br>**Radna temperatura:** -35°C ~ 60°C (-40°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)<br>**Dimenzije (ΦxV):** Φ108.5 x 81mm, težina: 0.45kg<br><br>**Kompatibilni nosači i pribor:** TR-UM06-E-IN, TR-UP06-IN, TR-A01-IN, TR-JB03-G-IN, TR-JB07/WM03-G-IN, TR-WM03-D-IN, TR-SE24-IN, TR-SE24-A-IN, TR-CM24-IN | 174,00 | 145,00 |
| **IPC325SS-DF28K-I0**<br> <br><br>unv®<br>Better Security, Better World. | 7656 | **IPC325SS-DF28K-I0**<br>**5Mpx Lighthunter Deep Learning AntiVandal Dome Mrežna kamera**<br><br>**Rezolucija snimanja:** 5MP(2592*1944),Max 20fps<br>**Čip**: 1/2.7", 5.0 megapixel, progressive scan, CMOS<br>**Šater**: Auto/Manual, 1 ~ 1/100000s<br>**Optika**: 2.8mm @F1.6<br>**Osetljivost**: Colour: 0.002Lux (F1.6, AGC ON) 0Lux with IR, IR<br>**IC domet**: do 50m<br>**Interfejsi**: 10/100M Base-TX Ethernet, Micro SD slot do 256GB, ANR, NAS (NFS), **Audio ulaz/izlaz 1/1, Alarmni ulaz/izlaz 1/1**<br>**Protokoli**: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, RTMP<br>**Mrežni standardi:** ONVIF (Profile S, Profile G, Profile T), API<br>**Kompresija:** Ultra 265, H.265, H.264, MJPEG<br>**Događaji: Motion detection, Audio detection, Tampering alarm**<br>**Smart funkcije: Cross Line detection, Intrusion detection, Enter Area detection, Leave Area detection (podržava klasifikaciju ljudi i vozila za ove funkcije), People counting, Object Removed, Object Left Behind, Face detection, People flow counting i Crowd Density monitoring**<br>**Ostale karakteristike:** 2D/3D DNR, HLC, BLC, Corridor mode 9:16, WDR 120db<br>**Zaštita**: IP67, IK10<br>**Napajanje i potrošnja:** DC 12V±25%, PoE (IEEE 802.3af), max 5W<br>**Radna temperatura:** -35°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)<br>**Dimenzije (ΦxV):** Φ109 x 81mm težina: 0,43kg<br><br>**Kompatibilni nosači i pribor:** TR-JB03-G-IN, TR-JB07/WM03-G-IN, TR-WM03-D-IN, TR-A01-IN , TR-UP06-IN , TR-UM06-E-IN | 234,72 | 195,60 |

| | | | | |
|---|---|---|---|---|
| **IPC3615SE-ADF28KM-WL-I0**<br> | 7058 | **IPC3615SE-ADF28KM-WL-I0**<br>**5 MP ColorHunter Fiksna Dome Mrežna Kamera**<br><br>**Rezolucija snimanja:** 5MP (2880*1620)@30/25fps; 4MP (2560*1440)@30/25fps<br>**Čip**: 1/2.7", 5.0 megapixel, progressive scan, CMOS<br>**Šater**: Auto/Manual, 1 ~ 1/100000s<br>**Optika**: 2.8mm @F1.0<br>**Osetljivost**: 0.001Lux (F1.0, AGC ON) 0Lux with IR on, IR-cut filter, WDR: 120db<br>**IC domet:** do 30m<br>**Interfejsi**: 10/100M Base-TX Ethernet, MicroSD, do 256GB<br>**Protokoli**: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS<br>**Mrežni standardi:** ONVIF (Profile S, Profile T), API<br>**Kompresija**: Ultra 265, H.265, H.264, MJPEG<br>**Smart funkcije: Motion detection, Tampering alarm, Audio detection, Cross line, Enter area, Leave area, Intrusion detection, Face detection**<br>**Ostale karakteristike: 2D/3D DNR, HLC, BLC, OSD, Privacy mask, ROI, 9:16 Corridor mod, Integrisan Mikrofon**<br>**Zaštita**: IP67<br>**Napajanje i potrošnja**: DC 12V±25%, PoE (IEEE 802.3af), max 7,5W<br>**Radna temperatura:** -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)<br>**Dimenzije (ΦxV):** Φ108.5 x 81mm,  težina: 0.45kg<br><br>**Kompatibilni nosači i pribor:** TR-UM06-E-IN, TR-UP06-IN, TR-A01-IN, TR-JB03-G-IN, TR-JB07/WM03-G-IN, TR-WM03-D-IN, TR-SE24-IN, TR-SE24-A-IN, TR-CM24-IN | 246,00 | 205,00 |
| **IPC2125SR3-ADUPF40**<br> | 6712 | **IPC2125SR3-ADUPF40**<br>**5 MP IR Fiksna Bullet Mrežna Kamera**<br><br>**Rezolucija snimanja:** 5MP (2592*1944) Max 20fps, 5MP (2592*1944), Max 25fps (WDR OFF);<br>**Čip:** 1/2.7", 5.0 megapixel, progressive scan, CMOS,<br>**Šater:** Auto/Manual, 1 ~ 1/100000s<br>**Optika:** 4.0mm@F1.6<br>**Osetljivost:** Colour: 0.005Lux (F1.6, AGC ON) 0Lux with IR on, IR-cut filter, 120db WDR<br>**IC domet:** do 30m<br>**Interfejsi:** 10/100M Base-TX Ethernet<br>**Protokoli:** IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS.<br>**Mrežni standardi:** ONVIF (Profile S, Profile T), API<br>**Kompresija:** Ultra 265, H.265, H.264, MJPEG<br>**Smart funkcije: Motion detection, tampering, audio loss detection, cross line, intrusion, object removed, object left behind, defocus, scene change, face, people counting**<br>**Ostale karakteristike: 2D/3D DNR, HLC, BLC, OSD, Privacy mask, ROI.**<br>**Zaštita:** IP67<br>**Napajanje i potrošnja:** DC 12V±25%, PoE (IEEE 802.3af), max 6W<br>**Radna temperatura:** -35°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)<br>**Dimenzije (DxŠxV):** 157.3 × 62.4 × 63mm, 0,45kg<br><br>**Kompatibilni nosači i pribor:** TR-UP06-B-IN, TR-A01-IN, TR-UP06-C-IN, TR-JB05-A-IN | 162,00 | 135,00 |
| **IPC2225SE-DF40K-WL-I0**<br> | 7062 | **IPC2225SE-DF40K-WL-I0**<br>**5 MP Colorhunter Fiksna Bullet Mrežna Kamera**<br><br>**Rezolucija snimanja:** 5MP (2880*1620)@30/25fps<br>**Čip**: 1/2,7", 5.0 megapixel, progressive scan, CMOS<br>**Šater**: Auto/Manual, 1 ~ 1/100000s<br>**Optika**: 4.0mm @F1.0<br>**Osetljivost**: 0.001Lux (F1.0, AGC ON) 0Lux with IR on, IR-cut filter, WDR: 120db<br>**IC domet**: do 30m<br>**Interfejsi**: 10/100M Base-TX Ethernet, **1xAlarmni ulaz, 1xAlarmni izlaz, Audio ulaz/izlaz x1**<br>**Protokoli**: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS<br>**Mrežni standardi**: ONVIF (Profile S, Profile T), API<br>**Skladistenje**:  MicroSD, do 256GB, ANR, NAS (NFS)<br>**Kompresija**: Ultra 265, H.265, H.264, MJPEG<br>**Smart funkcije: Motion detection,Tampering detection, Audio detection, Cross line, Intrusion detection, Enter area, Leave area, Alarm input/output**<br>**Ostale karakteristike:** 2D/3D DNR, HLC, BLC, OSD, Privacy mask, ROI.9:16 Corridor Mode<br>**Zaštita:** IP67, IK10<br>**Napajanje i potrošnja:** DC 12V±25%, PoE (IEEE 802.3af), max 9W<br>**Radna temperatura:** -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)<br>**Dimenzije (DxŠxV):** 245.6x85.7x85.4mm, težina: 0,92kg<br><br>**Kompatibilni nosači i pribor:** TR-JB07-D-IN, TR-JB06-A-IN, TR-UP06-B-IN, TR-UP06-C-IN, TR-A01-IN | 247,20 | 206,00 |

| | | | | |
|---|---|---|---|---|
| **IPC2325EBR5-DUPZ**<br> | 5591 | **IPC2325EBR5-DUPZ**<br>**5 MP IR Varifokalna Bullet Mrežna Kamera sa WDR-om**<br><br>**Rezolucija snimanja:** 5MP (2592*1944), Max 20fps; 5MP (2592*1944), Max 25fps (WDR OFF)<br>**Čip:** 1/2.7", 5.0 megapixel, progressive scan, CMOS<br>**Šater:** Auto/Manual, 1 ~ 1/100000s<br>**Optika:** 2.7 ~ 13.5mm, AF automatski fokus motorizovanim zoom-om<br>**Osetljivost:** 0.002Lux (F1.2, AGC ON) 0Lux with IR on, IR-cut filter,**WDR: 120db**<br>**IC domet:** do 50m<br>**Interfejsi:** 10/100M Base-TX Ethernet, MicroSD, do 256GB, 2x Audio ulaz, 1x Audio izlaz, 1x Alarm ulaz, 1x Alarmni izlaz<br>**Protokoli:** IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS.<br>**Mrežni standardi:** ONVIF (Profile S, Profile T, Profile G), API<br>**Kompresija:** Ultra 265, H.265, H.264, MJPEG<br>**Smart funkcije: Intrusion Detection, Motion detection,Tampering alarm, Line Crossing, Face detection, Audio Detection.**<br>**Inteligentne indentifikacije: Defocus, Promena scene, Ostavljeni objekat, Pomereni objekat.**<br>**Statističke analize: Brojanje Ljudi**<br>**Ostale Karakteristike: 2D/3D DNR, HLC, BLC, OSD, Privacy mask, ROI, 9:16 Corridor mod**<br>**Zaštita:** IP67P67<br>**Napajanje i potrošnja:** DC 12V±25%, PoE (IEEE 802.3af), max 10W<br>**Radna temperatura:** -35°C ~ 60°C (-40°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)<br>**Dimenzije (DxŠxV):** 253.4 × 86 × 71.7mm, težina: 1kg<br><br>**Kompatibilni nosači i pribor:** TR-UP06-B-IN, TR-A01-IN, TR-JB07-D-IN, TR-UP06-CIN, TR-JB06-A-IN | 294,00 | 245,00 |
| **IPC3635ER3-DUPZ**<br> | 5860 | **IPC3635ER3-DUPZ**<br>**5 MP IR Varifokalna Dome Mrežna Kamera sa WDR-om**<br><br>**Rezolucija snimanja:** 5MP (2592*1944), Max 20fps; 5MP (2592*1944), Max 25fps (WDR OFF)<br>**Čip:** 1/2.7", 5.0 megapixel, progressive scan, CMOS<br>**Šater:** Auto/Manual, 1 ~ 1/100000s<br>**Optika:** 2.7 ~ 13.5mm, AF automatski fokus motorizovanim zoom-om<br>**Osetljivost:** 0.002Lux (F1.2, AGC ON) 0Lux with IR on, IR-cut filter, WDR: 120db<br>**IC domet:** do 30m<br>**Interfejsi:** 10/100M Base-TX Ethernet, MicroSD, do 256GB, ugrađen mikrofon<br>**Protokoli:** IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS.<br>**Mrežni standardi:** ONVIF (Profile S, Profile T, Profile G), API<br>**Kompresija:** Ultra 265, H.265, MJPEG<br>**Smart funkcije: Intrusion Detection, Motion detection,Tampering alarm, Line Crossing, Face detection, Audio Detection.**<br>**Inteligentne indentifikacije: Defocus, Promena scene, Ostavljeni objekat, Pomereni objekat.,**<br>**Statističke analize: Brojanje Ljudi**<br>**Ostale Karakteristike: 2D/3D DNR, HLC, BLC, OSD, Privacy mask, ROI, 9:16 Corridor mod**<br>**Zaštita:** IP67<br>**Napajanje i potrošnja:** DC 12V±25%, PoE (IEEE 802.3af), max 8,16W<br>**Radna temperatura:** -40°C ~ 60°C (-40°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)<br>**Dimenzije (ΦxV):** Φ129 x 110mm, težina: 0.82kg<br><br>**Kompatibilni nosači i pribor:** TR-WM03-B-IN, TR-UP06-IN, TR-A01-IN, TR-JB03-H-IN, TR-SE24-IN, TR-SE24-A-IN, TR-CM24-IN, TR-JB07/WM03-F-IN. | 294,00 | 245,00 |
| **IPC815SR-DVPF14**<br> | 6451 | **IPC815SR-DVPF14**<br>**Fisheye IP kamera**<br>**Čip**: Image sensor 1/2.8", progressive scan, 5.0 megapixel, CMOS<br>**Panoramic image: 360 stepeni**<br>**Optika:** 1.4mm@F2.0<br>**Rezolucija snimanja**: 2592x1944 resolution, 30fps<br>**Osetljivost:** Colour: 0.01 Lux (F2.0, AGC ON) 0 Lux with IR, WDR 120db<br>**Interfejsi:** 1x RJ45, Slot za SD karticu do 256GB,<br>**Protokoli:** IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS.<br>**Mrežni standardi:** ONVIF<br>**Smart funkcije: Motion detection, Tampering alarm, Heat map, Integrisan mikrofon**<br>**Kompresija:** H.265, H.264, MJPEG<br>**IC osvetljenje:** Domet IC dioda do 10m<br>**Zaštita:** IP67, IK10<br>**Napajanje i potrošnja:** DC 12V±25%, PoE (IEEE 802.3af), max 5W<br>**Radna Temperatura:** -40°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)<br>**Dimenzije:** Φ125 × 43.7 mm (Φ4.9" × 1.7")<br>**Kompatibilni nosači i pribor:** TR-A01-IN, TR-JB03-H-IN, TR-SE24-IN, TR-SE24-A-IN, TR-CM24-IN | 300,00 | 250,00 |

# IP KAMERE 8 MPX UNIVIEW

| NAZIV ARTIKLA | Kat. br. | Karakteristike | CENA EUR (gotovinski) | CENA EUR (racun bez PDV) |
|---|---|---|---|---|
| **IPC2128LE-ADF28KM-G**<br> <br>Better Security, Better World. | 7652 | **IPC2128LE-ADF28KM-G**<br>**4K Mini Fiksna Bullet Mrežna kamera**<br><br>**Rezolucija snimanja:** 8MP (3840*2160), Max 20fps<br>**Čip**: 1/2.7", 8.0 megapixel, progressive scan, CMOS<br>**Šater**: Auto/Manual, 1 ~ 1/100000s<br>**Optika**: 2.8mm@F1.6<br>**Osetljivost**: podržava Easystar: Colour: 0.005Lux ( F1.6, AGC ON), 0Lux with IR on<br>**IR domet:** do 50m<br>**Interfejsi**: 10/100M Base-TX Ethernet, **integrisan mikrofon**, SD kartica do 256GB, ANR, NAS (NFS)<br>**Protokoli:** IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL/TLS, QoS, 802.1x, SNMP<br>**Mrežni standardi:** ONVIF (Profile S, Profile G, Profile T), API , SDK<br>**Kompresija**: Ultra 265, H.265, H.264, MJPEG<br>**Događaji**: **Motion detection, tampering alarm, audio detection**<br>**Smart funkcije: Cross line detection, Intrusion detection**<br>**Ostale karakteristike:** 2D/3D DNR, HLC, BLC, Privacy mask, Flip, corridor mode 9:16, 120dB WDR<br>**Zaštita**: IP67<br>**Napajanje i potrošnja:** DC 12V±25%, PoE (IEEE 802.3af), max 7W<br>**Radna temperatura:** -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)<br>**Dimenzije (DxŠxV):** 190×73×71mm,  0,45kg<br>**Kompatibilni nosači i pribor:** TR-JB05-B-IN, TR-UP06-C-IN, TR-A01-IN | 211,20 | 176,00 |
| **IPC3618SR3-DPF28M**<br> <br>Better Security, Better World. | 5862 | **IPC3618SR3-DPF28M**<br>**4K IR Fiksna Turret Mrežna Kamera sa WDR-om**<br><br>**Rezolucija snimanja:** 8MP (3840*2160), Max 20fps<br>**Čip:** 1/2.5", 8.0 megapixel, progressive scan, CMOS<br>**Šater:** Auto/Manual, 1 ~ 1/100000s<br>**Optika:** 2.8mm @F2.0<br>**Osetljivost:** 0.05Lux (F 2.0, AGC ON) 0Lux with IR on, IR-cut filter, **WDR: 120db**<br>**IC domet:** do 30m<br>**Interfejsi:** 10/100M Base-TX Ethernet<br>**Protokoli:** IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS.<br>**Mrežni standardi:** ONVIF (Profile S, Profile T), API<br>**Kompresija:** Ultra 265, H.265, H.264, MJPEG<br>**Smart funkcije: Intrusion Detection, Motion detection, Tampering alarm, Line Crossing, Face detection, Audio Detection.**<br>**Inteligentne indentifikacije: Defocus, Promena scene, Ostavljeni objekat, Pomereni objekat.**<br>**Statističke analize: Brojanje Ljudi**<br>**Ostale Karakteristike: 2D/3D DNR, HLC, BLC, OSD, Privacy mask, ROI, 9:16 Corridor mod**<br>**Zaštita:** IP67<br>**Napajanje i potrošnja:** DC 12V±25%, PoE (IEEE 802.3af), max 5,5W<br>**Radna temperatura:** -30°C ~ 60°C (-40°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)<br>**Dimenzije (ΦxV):** Φ126 x 94mm, težina: 0.45kg<br><br>**Kompatibilni nosači i pribor:** TR-WM03-B-IN, TR-UP06-IN, TR-A01-IN, TR-JB03-H-IN, TR-SE24-IN, TR-SE24-A-IN, TR-CM24-IN, TR-JB07/WM03-F-IN | 184,20 | 153,50 |

| | | | | |
|---|---|---|---|---|
| **IPC328LE-ADF28K-G**<br> <br><br>unv®<br>Better Security, Better World. | 7651 | **IPC328LE-ADF28K-G**<br>**4K Anti-vandal IR Fiksna Dome Mrežna kamera**<br><br>**Rezolucija snimanja**: 8MP (3840*2160), Max 20fps<br>**Čip**: 1/2.7", 8.0 megapixel, progressive scan, CMOS<br>**Šater**: Auto/Manual, 1 ~ 1/100000s<br>**Optika**: 2.8mm @F1.6 fixed-focal<br>**Osetljivost**: podržava Easystar: Colour: 0.005Lux ( F1.6, AGC ON), 0Lux with IR on<br>**IC domet:** do 30m<br>**Interfejsi**: 10/100M Base-TX Ethernet, Micro SD slot do 256GB, ANR, NAS (NFS), **integrisan mikrofon**<br>**Protokoli**: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, **RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL/TLS, 802.1x, SNMP**<br>**Mrežni standardi:** ONVIF (Profile S, Profile G, Profile T), API, SDK<br>**Kompresija**: Ultra 265, H.265, H.264, MJPEG<br>**Događaji: Motion detection, tampering alarm, audio detection**<br>**Smart funkcije: Cross Line detection, Intrusion detection**<br>**Ostale karakteristike: 2D/3D DNR, HLC, BLC, WDR:120db, Corridor mode 9:16**<br>**Zaštita:** IP67, IK10<br>**Napajanje i potrošnja:** DC 12V±25%, PoE (IEEE 802.3af), max 4.5W<br>**Radna temperatura:** -30°C ~ 60°C (-22°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)<br>**Dimenzije (ΦxV):** Φ109 x 83mm, težina: 0,37kg<br><br>**Kompatibilni nosači i pribor:** TR-JB03-G-IN, TR-JB07/WM03-G-IN, TR-WM03-D-IN, TR-A01-IN, TR-UM06-E-IN, TR-UP06-IN, TR-SE24-IN, TR-SE24-A-IN, TR-CM24-IN | 216,00 | 180,00 |
| **IPC3238ER3-DVZ**<br> <br><br>unv®<br>Better Security, Better World. | 5874 | **IPC3238ER3-DVZ**<br>**4K IR Varifokalna Dome Mrežna Kamera sa WDR-om**<br><br>**Rezolucija snimanja:** 8MP (3840*2160), Max 30fps; 2MP (1920*1080), Max 30fps<br>**Čip:** 1/2.5", 8.0 megapixel, progressive scan, CMOS<br>**Šater:** Auto/Manual, 1 ~ 1/100000s<br>**Optika:** 2.8 ~ 12mm@F1.6<br>**Osetljivost:** 0.02Lux (F1.2, AGC ON) 0Lux with IR on, IR-cut filter, **WDR: 120db**<br>**IC domet:** do 30m<br>**Interfejsi:** 10/100M Base-TX Ethernet, Micro SD slot do 256GB, 1x Audio ulaz, 1x Audio izlaz, 1x Alarmni ulaz, 1x Alarmni izlaz, BNC izlaz, DC12V izlaz sa PoE napajanjem.<br>**Protokoli:** IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS.<br>**Mrežni standardi:** ONVIF (Profile S, Profile T), API<br>**Kompresija:** Ultra 265, H.265, H.264, MJPEG<br>**Smart funkcije: Intrusion Detection, Motion detection, Tampering alarm, Line Crossing, Face detection, Audio Detection.**<br>**Inteligentne identifikacije: Defocus, Promena scene, Ostavljeni objekat, Pomereni objekat.,**<br>**Statističke analize: Brojanje Ljudi**<br>**Ostale karakteristike: 2D/3D DNR, HLC, BLC, OSD, Privacy mask, ROI, 9:16 Corridor mod**<br>**Zaštita:** IP67, IK10<br>**Napajanje i potrošnja:** DC 12V±25%, PoE (IEEE 802.3af), max 8,7W<br>**Radna temperatura:** -40°C ~ 60°C (-40°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)<br>**Dimenzije (ΦxV):** Φ148 x 111.3mm, težina: 0.92kg<br><br>**Kompatibilni nosači i pribor:** TR-FM152-A-IN, TR-WM04-IN, TR-UP06-IN, TR-SM04-IN, TR-A01-IN, TR-JB04-C-IN, TR-JB/WM04-B-IN | 780,00 | 650,00 |

| | | | | |
|---|---|---|---|---|
| **IPC268ER9-DZ**<br> <br>Better Security, Better World. | 5881 | **IPC268ER9-DZ**<br>**4K IR Varifokalna Bullet Mrežna Kamera sa WDR-om**<br><br>**Rezolucija snimanja:** 8MP (3840*2160), Max 30fps; 2MP (1920*1080), Max 30fps<br>**Čip:** 1/2.5", 8.0 megapixel, progressive scan, CMOS<br>**Šater:** Auto/Manual, 1 ~ 1/100000s<br>**Optika:** 2.8 ~ 12mm@F1.6, P-Iris, AF Automatski fokus sa motorizovanim zoom-om<br>**Osetljivost:** 0.02Lux (F1.2, AGC ON) 0Lux with IR on, IR-cut filter, WDR: 120db<br>**IC domet:** do 100m<br>**Interfejsi:** 10/100M Base-TX Ethernet, Micro SD slot do 256GB, 1x Audio ulaz, 1x Audio izlaz, 2x Alarmni ulaz, 1x Alarmni izlaz, BNC izlaz, 1x RS485, Audio kabl<br>**Protokoli:** IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS.<br>**Mrežni standardi:** ONVIF (Profile S, Profile T, Profile G), API<br>**Kompresija:** Ultra 265, H.265, H.264, MJPEG<br>**Smart funkcije: Intrusion Detection, Motion detection, Tampering alarm, Line Crossing, Face detection, Audio Detection.**<br>**Inteligentne indentifikacije: Defocus, Promena scene, Ostavljeni objekat, Pomereni objekat.,**<br>**Statističke analize: Brojanje Ljudi**<br>**Ostale karakteristike: 2D/3D DNR, HLC, BLC, OSD, Privacy mask, ROI, 9:16 Corridor mod**<br>**Zaštita:** IP67<br>**Napajanje i potrošnja:** DC 12V±25%, PoE (IEEE 802.3at), max 13,7W<br>**Radna temperatura:** -40°C ~ 60°C (-40°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)<br>**Dimenzije (DxŠxV):** 305.5 × 104.1 × 97.3mm, težina: 1.65kg<br><br>**Kompatibilni nosači i pribor:** TR-UP06-B-IN, TR-A01-IN, TR-JB07-D-IN, TR-UP06-C-IN, TR-JB06-A-IN | 780,00 | 650,00 |

# KONFERENCIJSKE KAMERE

| NAZIV ARTIKLA | Kat. br. | Karakteristike | CENA EUR (gotovinski) | CENA EUR (racun bez PDV) |
|---|---|---|---|---|
| **IoT-UNEAR A30T konferencijska kamera**<br> <br>Better Security, Better World. | 6941 | **IoT-UNEAR A30T konferencijska kamera**<br>**IoT-Unear A30T All-In-One Video Konferencijska Kamera**<br>**Kamera:** Full HD 1080P@30fps,<br>Ugao gledanja horizotalini FOV 100°,<br>16:9 Aspect ratio,<br>Automatski balans i ekspozitura,<br>Fiksni fokus<br>**Mikrofon:**<br>4 omnidirekciona mikrofona,<br>Domet do 5m<br>**Zvučnici:**<br>Izlazna snaga 3W, frekvencijski raspon 20Hz-20kHz<br>**Ostalo:**<br>Ulaz 5V-500mA,<br>Povezivanje USB tip-C (dolazi u pakovanju),<br>Dimenzije: 270mm (visina) x 110mm (prečnik),<br>Težina 618g,<br><br>Plug & play, opšta kompatibilnost sa vodećim mrežnim platformama za konferencije. | 240,00 | 200,00 |

# PTZ UNIVIEW

| NAZIV ARTIKLA | Kat. br. | Karakteristike | CENA EUR (gotovinski) | CENA EUR (racun bez PDV) |
|---|---|---|---|---|
| **IPC6415SR-X5UPW**<br> <br>Better Security, Better World. | 6450 | **IPC6415SR-X5UPW**<br>**5 MP Unutrašnja mini PTZ IP kamera**<br><br>**Rezolucija snimanja:** 5MP (2592*1944):Max. 30 fps<br>**Čip:** 1/2.7", 5.0 megapixel, progressive scan, CMOS<br>**Šater:** Auto/Manual, 1 ~ 1/100000s<br>**Optika:** 2.7~13.5mm, AF automatski fokus sa motorizovanim zoom-om<br>**Osetljivost:** 0.002Lux (F1.2, AGC ON) 0Lux with IR on, IR-cut filter,<br>**IR domet:** do 30m<br>**Interfejsi:** 10/100M Base-TX Ethernet, Micro SD slot do 256GB, **ugrađen mikrofon i zvučnik**<br>**PTZ komande:** 1024 preseta, Home pozicija.<br>**Protokoli:** IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS.<br>**Mrežni standardi:** ONVIF (Profile G, Profile S, Profile T), API<br>**Kompresija:** Ultra 265, H.265, H.264, MJPEG<br>**Smart funkcije:** **Motion detection, line crossing, intrusion detection, ulaz i izlaz iz oblasti, object left behind i object removed, face detection, people counting, defocus i promena scene**<br>**Ostale karakteristike:** **2D/3D DNR, HLC, BLC, OSD, Privacy mask, ROI, EIS, DWDR**<br>**Napajanje i potrošnja:** DC 12V±25%, PoE (IEEE802.3 af), 12W<br>**Radna Temperatura:** -10°C ~ 50°C (-40°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)<br>**Dimenzije (ΦxV):** Φ129mm×143mm, težina: 0.75kg<br>**Može da radi samostalno sa EZview!** | 264,00 | 220,00 |
| **IPC672LR-AX4DUPKC**<br> <br>Better Security, Better World. | 6616 | **IPC672LR-AX4DUPKC**<br>**2 MP Outdoor mini PTZ kamera sa integrisanom sirenom**<br><br>**Rezolucija snimanja:** 1080P (1920*1080), Max 30fps<br>**Čip:** 1/2.8", progressive scan , 2.0 megapixel, CMOS<br>**Shutter:** Auto/Manual, 1 ~ 1/100000s<br>**Optika:** 2.8-12mm AF automatsko fokusiranje i motorizovan 4x opticki zoom<br>**Osetljivost:** 0.001Lux ( F1,6, AGC ON) 0Lux with IR on, IR-cut filter<br>**IC domet:** do 50m<br>**Interfejsi:** 10/100M Base-TX Ethernet, Micro SD slot do 128GB<br>**Protokoli:** IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP , PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP , 802.1x , SNMP, SSL<br>**Mrežni standardi:** ONVIF(Profile S, Profile G, Profile T), API<br>**PTZ funkcije:** Preset patrol, Route patrol (256 preseta)<br>**Kompresija:** Ultra 265, H.265, H.264, MJPEG<br>**Smart funkcije:** **Motion detection,Tampering alarm, Audio Detection, Human body detection i Auto tracking**<br>**Kamera poseduje integrisanu sirenu od 52db, kao i mikrofon i zvučnik sa mogućnošću da se izabere jedna od 10 poruka na engleskom da upozori uljeza ukoliko upadne u nedozvoljeno područje (moguće ubaciti jednu poruku na srpskom ili nekom drugom jeziku)**<br>**Zaštita:** IP66<br>**Napajanje i potrošnja:** DC 12V±25%, PoE (IEEE802.3 at)<br>**Radna Temperatura:** -20°C ~ 60°C (-4°F to 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)<br>**Dimenzije:** Φ133mm*269.4mm (Φ5.2”x 10.6”)<br><br>**Kompatibilni nosači i pribor:** TR-JB07-D-IN, TR-UP06-B-IN, TR-UP06-C-IN, TR-A01-IN | 276,00 | 230,00 |

| | | | | |
|---|---|---|---|---|
| **UNV IPC6312LFW-AX4C-VG 2MP**<br> | 7655 | **UNV IPC6312LFW-AX4C-VG 2MP**<br>**2 MP Outdoor mini PTZ kamera sa integrisanom sirenom**<br>**Rezolucija snimanja:** 1080P (1920*1080), Max 30fps<br>**Čip:** 1/2.7", progressive scan , 2.0 megapixel, CMOS<br>**Shutter:** Auto/Manual, 1 ~ 1/100000s<br>**Optika:** 2.8-12mm AF automatsko fokusiranje i motorizovan 4x opticki zoom<br>**Osetljivost:** Colour: 0.002Lux (F1.6, AGC ON) 0Lux with IR on<br>**IC domet:** do 50m<br>**Interfejsi:** 10/100M Base-TX Ethernet, Micro SD slot do 256GB, ANR, NAS(NFS)<br>**Protokoli:** IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP , PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP , 802.1x , SNMP, SSL<br>**Mrežni standardi:** ONVIF(Profile S, Profile G, Profile T), API<br>**PTZ funkcije:** Preset patrol (16 patrola do 64 preseta)<br>**Kompresija:** Ultra 265, H.265, H.264, MJPEG<br>**Smart funkcije: Motion detection,Tampering alarm, Audio Detection i Auto tracking**<br>**Smart intrusion prevention: cross line detection, intrusion detection, enter area, leave are detection**<br>**Kamera poseduje integrisanu sirenu od 52db, kao i mikrofon i zvucnik sa mogucnoscu da se izabere jedna od 10 poruka na engleskom da upozori uljeza ukoliko upadne u nedozvoljeno podrucje (moguce ubaciti jednu poruku na srpskom ili nekom drugom jeziku)**<br>**Zaštita:** IP66<br>**Napajanje i potrošnja:** DC 12V±25%, PoE (IEEE802.3 at)<br>**Radna temperatura:** -20°C ~ 60°C (-4°F to 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)<br>**Dimenzije:** Φ133mm*269.4mm (Φ5.2”x 10.6”)<br>**Kompatibilni nosači i pribor:** TR-JB07-D-IN, TR-UP06-B-IN, TR-UP06-C-IN, TR-A01-IN | 324,00 | 270,00 |
| **IPC9312LFW-AF28-2X4**<br> | 7504 | **IPC9312LFW-AF28-2X4**<br>**2*2 MP Lighthunter Dual-Lens Mrežna PTZ Kamera**<br><br>**Rezolucija snimanja:** 1080P (1920*1080), Max 25fps<br>**Čip:** 1/2.8", 2.0 megapixel, CMOS<br>**Shutter:** Auto/Manual, 1 ~ 1/100000s<br>**Optika:** 2.8mm@F1.6 - fiksna kamera<br>2.8mm-12mm@F1.6 automatski fokus i 4x motorizovani zoom - PTZ kamera<br>**Osetljivost:** Color:0.002 lux (F1.6, AGC ON), 0 lux sa IR - Fiksna kamera<br>Color:0.002 lux (F1.6, AGC ON), 0 lux sa IR/Warm light - PTZ kamera<br>**IR domet: do 10m** - Fiksna kamera<br>**do 50m** Warm light domet do 10m - PTZ kamera<br>**Interfejsi:** 10/100M Base-TX Ethernet, Micro SD slot do 256GB<br>**Protokoli:** IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, RTMP, SSL/TLS<br>**Mrežni standardi:** ONVIF (Profile S, Profile G), API, SDK<br>**PTZ funkcije:** Preset patrol, Route patrol (255 preseta)<br>**Kompresija:** Ultra 265, H.265, H.264, MJPEG<br>**Smart funkcije: Audio detekcija, Cross line, Enter area, Leave area, Intrusion, Master-slave linkage**<br>**Kamera poseduje integrisanu sirenu od 52db, kao i mikrofon i zvučnik sa mogućnošću da se**<br>**izabere jedna od 10 poruka da upozori uljeza ukoliko upadne u nedozvoljeno područje**<br>**(moguće ubaciti jednu snimljenu poruku)**<br>**Ostale funkcije:** Integrisana 2 mikforona i zvučnik, ANR, NAS (NFS), 120dB WDR,<br>**Zaštita:** IP66<br>**Napajanje i potrošnja:** DC 12V±25%, PoE (IEEE802.3 at)<br>**Radna temperatura:** -20°C ~ 60°C (-4°F to 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)<br>**Dimenzije:** Φ134 x 192 x 302mm zidna montaža, Φ134 x 154 x 363mm plafonska montaža, 1,03kg | 378,00 | 315,00 |

| | | | | |
|---|---|---|---|---|
| **IPC675LFW-AX4DUPKC-VG**<br> <br><br>unv®<br>Better Security, Better World. | 6800 | **IPC675LFW-AX4DUPKC-VG**<br>**5 MP Outdoor mini PTZ kamera sa integrisanom sirenom**<br><br>**Rezolucija snimanja:** 5MP (2880*1620), Max 30fps<br>**Čip:** 1/2.7", progressive scan , 5.0 megapixel, CMOS<br>**Shutter:** Auto/Manual, 1 ~ 1/100000s<br>**Optika:** 2.8-12mm AF automatsko fokusiranje i motorizovan 4x opticki zoom<br>**Osetljivost:** 0.003Lux ( F1,6, AGC ON) 0Lux with IR on, IR-cut filter, IC domet do 50m<br>**Interfejsi:** 10/100M Base-TX Ethernet, Micro SD slot do 256GB<br>**Protokoli: I**Pv4, IGMP, ICMP, ARP, TCP, UDP, DHCP , PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP , 802.1x , SNMP, SSL<br>**Mrežni standardi:** ONVIF(Profile S, Profile G, Profile T), API<br>**PTZ funkcije:** Preset patrol, Route patrol (256 preseta)<br>**Kompresija:** Ultra 265, H.265, H.264, MJPEG<br>**Smart funkcije: Motion detection,Tampering alarm, Audio Detection, Cross Line, Intrusion, Enter Area, Leave Area detection, Auto tracking**<br>**Poseduje tzv Smart intrusion prevention koji značajno smanjuje lažne alarme izazvane lišćem, pticama i svetlom... fokusirajući se na ljude, vozila i druga nemotorna vozila.**<br>**Kamera poseduje integrisanu sirenu od 52db, kao i mikrofon i zvučnik sa mogućnošću da se izabere jedna od 10 poruka na engleskom da upozori uljeza ukoliko upadne u nedozvoljeno područje.**<br>**(moguće ubaciti jednu poruku na srpskom ili nekom drugom jeziku)**<br>**Zaštita:** IP66<br>**Napajanje i potrošnja:** DC 12V±25%, PoE (IEEE802.3 at)<br>**Radna Temperatura:** -20°C ~ 60°C (-4°F to 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)<br>**Dimenzije:** Φ133mm*269.4mm (Φ5.2”x 10.6”)<br><br>**Kompatibilni nosači i pribor:** TR-JB07-D-IN, TR-UP06-B-IN, TR-UP06-C-IN, TR-A01-IN | 360,00 | 300,00 |
| **IPC6612SR-X25-VG**<br> <br><br>unv®<br>Better Security, Better World. | 7285 | **IPC6612SR-X25-VG**<br>**2 MP Lighthunter PTZ kamera sa 25x optičkim zoom-om**<br><br>**Rezolucija snimanja:** 2MP (1920*1080), Max 30fps<br>**Čip:** 1/2.8", 2.0 megapixel, progressive scan, CMOS, Blenda:F1.5 ~ F3.0<br>**Šater:** Auto/Manual, 1 ~ 1/100000s<br>**Optika:** 5~ 125mm, AF automatski fokus sa motorizovanim zoom-om<br>**Osetljivost:** 0.001Lux (F1.5, AGC ON) 0Lux with IR on, IR-cut filter, WDR: 120db<br>**IR domet:** do 150 m<br>**Interfejsi:** 10/100M Base-TX Ethernet, Micro SD slot do 256GB, 1x Audio ulaz, 1x Audio izlaz, 2x Alarmni ulaz, 1x Alarmni izlaz. 1x RS485<br>**PTZ komande:** Preset Patrol, 1024 preseta, Home pozicija.<br>**Protokoli:** IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, RTMP,SSL/TLS<br>**Mrežni standardi:** ONVIF (Profile G, Profile S, Profile T), API<br>**Kompresija:** Ultra 265, H.265, H.264, MJPEG<br>**Smart funkcije: Motion detection, audio detection, tampering alarm, Smart intrusion prevention, Auto tracking**<br>**Ostale karakteristike: 2D/3D DNR, HLC, BLC, OSD, Privacy mask, ROI, EIS**<br>**Zaštita:** IP66<br>**Napajanje:** DC 12V±10%,PoE+ (IEEE802.3 at)<br>**Radna temperatura:** -40°C ~ 65°C (-40°F ~ 149°F), Vlažnost: ≤95% RH (ne kondenzujuće)<br>**Dimenzije (ΦxV):** Φ220 × 369mm, težina: 3,3kg<br><br>**Kompatibilni nosači i pribor:** TR-CE45-IN, TR-UF45-A-IN, TR-SE45-IN, TR-SE45-A-IN, TR-WE45-IN, TR-WE45-A-IN, TR-WE45-B-IN, TR-JB12-IN, TR-UP08-A-IN, TR-UC08-A-IN, TR-UP08-B-IN, TR-UC08-B-IN | 864,00 | 720,00 |

| | | | | |
|---|---|---|---|---|
| **IPC6222ER-X30-B**<br> <br> | 5876 | **IPC6222ER-X30-B**<br>**2 MP Speed Dome PTZ kamera sa 30x optičkim zoom-om**<br><br>**Rezolucija snimanja:** 2MP (1920*1080), Max 30fps<br>**Čip:** 1/2.8", 2.0 megapixel, progressive scan, CMOS<br>**Šater:** Auto/Manual, 1 ~ 1/100000s<br>**Optika:** 4.5 ~ 135mm, AF automatski fokus sa motorizovanim zoom-om od 30x<br>**Osetljivost:** 0.001Lux (F1.5, AGC ON) 0Lux with IR on, IR-cut filter, WDR: 120db<br>**IC domet: do 150m**<br>**Interfejsi:** 10/100M Base-TX Ethernet, Micro SD slot do 256GB, 1x Audio ulaz, 1x Audio izlaz, 1x Alarmni ulaz, 1x Alarmni izlaz, Audio kabl<br>**PTZ komande:** 16 patrola i 32 preseta po patroli, Home pozicija.<br>**Protokoli:** IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS.<br>**Mrežni stadardi:** ONVIF (Profile G, Profile S, Profile T), API<br>**Kompresija:** Ultra 265, H.265, H.264, MJPEG<br>**Smart funkcije: Intrusion Detection, Motion detection,Tampering alarm, Line Crossing, Face detection, Audio Detection, Digitalni zoom 16x, Auto tracking**<br>**Inteligentne indentifikacije: Defocus, Promena scene, Ostavljeni objekat, Pomereni objekat.,**<br>**Statističke analize: Brojanje Ljudi**<br>**Ostale Karakteristike: 2D/3D DNR, HLC, BLC, OSD, Privacy mask, ROI, EIS**<br>**Zaštita: IP66**<br>**Napajanje i potrošnja:** AC 24V±25%, DC 24V±25%, PoE (PSE Required), 9 ~ 42W<br>**Radna temperatura:** -40°C ~ 60°C (-40°F ~ 140°F), Vlažnost: ≤95% RH (ne kondenzujuće)<br>**Dimenzije:** (ΦxV):Ø 227 x 359.4mm, težina: 5.28kg<br><br>**Kompatibilni nosači i pribor:** TR-CE45-IN, TR-UF45-A-IN, TR-SE45-IN, TR-SE45-A-IN, TR-WE45-IN, TR-WE45-A-IN, TR-WE45-B-IN, TR-JB12-IN, TR-UP-A-IN, TR-UC08-A-IN, TR-UP08-B-IN, TR-UC08-BIN | 840,00 | 700,00 |

# SERVER UNICORN

| NAZIV ARTIKLA | Kat. br. | Karakteristike | CENA EUR (gotovinski) | CENA EUR (racun bez PDV) |
|---|---|---|---|---|
| **Server UNICORN**<br> <br>unv® Better Security, Better World. | 6335 | **Server UNICORN**<br>**Glavne Karakteristike**<br>**Stability:** Linux OS, dual-BIOS, redundant power, two-server hot standby<br>**Compatibility:** Third-party IP Cameras supported with standard ONVIF<br>**Access:** Browser/Server, Client/Server and mobile clients (both iOS and Android)<br>**Connection:** 1000 device connections, up to 2000 channels of high-definition network videos<br>**Management:** Unified management of NVR, IPC, decoder, network keyboard, cloud devices, alarm control panel and door access control, support devices' configuration import/export<br>**Storage:** Max 16 hard disks and 2 disk enclosures; expandable up to 48 disks with 672TB storage, recording backup, IPSAN storage<br>**Decoding:** Max 16×1080P decoding outputs in three screens, expandable up to 112×1080P in 15 screens with 2 decoding cards inserted<br>**Service:** Live view, playback, sequence, video wall, E-map, two-way audio, and alarm plan<br>**Reliability:** Support of HTTPS, 802.1x authentication, ARP protection, Telnet enabling/disabling, network fault tolerance, multi-IP configuration, load balancing, secure password and IP address filtering<br><br>**Height:** 3U, support mounting in standard 19" cabinet<br>477.1 mm × 481.6 mm × 130.5 mm (18.8''×19''×5.1'') (including front panel) | 6189,60 | 5158,00 |
| **PWR-300A-IN**<br> <br>unv® Better Security, Better World. | 7288 | **PWR-300A-IN**<br>**Rezervno napajanje za UNICORN**<br><br>Reduntantno napajanje za snimače koji imaju veliki kapacitet HDD-a<br>Poseduje LED indikatore za normalna i abnormalna stanja<br>Radna temperatura: 0 ~ 55℃<br>Dimenzije: 234.9 × 40.13 × 101.6mm | 322,00 | 268,33 |

# SWITCH UREĐAJI

| NAZIV ARTIKLA | Kat. br. | Karakteristike | CENA EUR (gotovinski) | CENA EUR (racun bez PDV) |
|---|---|---|---|---|
| **NSW2010-6T-POE-IN**<br> | 6232 | **NSW2010-6T-POE-IN**<br>**6×100Mbps network ports (RJ45), od toga 4 PoE porta**<br>**Podržava:**<br>IEEE802.3,IEEE802.3u,IEEE802.3az,IEEE802.3x,IEEE802.3af,IEEE802.3at<br>**Modovi rada:**<br>**Default(Normal mode):** Svi portovi komuniciraju normalno međusobno<br>**EXTEND(Surveillance mode)**: Distanca prenosa do 250 metara uz brzinu 10Mb/s.<br>**6kV zaštita od prenapona**<br>**PoE Budžet:** 65W<br>**Maksimalna snaga porta:** 30W<br>**Dimenzije:** 160mm x 93mm x 32mm | 68,40 | 57,00 |
| **NSW2010-10T-POE-IN**<br> | 6235 | **NSW2010-10T-POE-IN**<br>**10×100Mbps network ports (RJ45), od toga 8 PoE porta**<br>**Podržava:**<br>IEEE802.3,IEEE802.3u,IEEE802.3az,IEEE802.3x,IEEE802.3af,IEEE802.3at<br>**Modovi rada:**<br>**Default(Normal mode)**: Svi portovi komuniciraju normalno međusobno<br>**EXTEND(Surveillance mode**): Distanca prenosa do 250 metara uz brzinu 10Mb/s.<br>**VLAN(Secure mode):** 8 Downlink portova mogu komunicirati samo sa uplink portovima.<br>**6kV zaštita od prenapona**<br>**PoE Budžet:** 120W<br>**Maksimalna snaga porta:** 30W<br>**Dimenzije:** 220mm x 150mm x 44mm<br>Moguća rek montaža 19'' , dolazi uz switch | 140,40 | 117,00 |
| **NSW2010-16T2GC-POE-IN**<br> | 6334 | **NSW2010-16T2GC-POE-IN**<br>**16×100Mbps network ports (RJ45), 2x1000Mbps uplink porta (RJ45), 2x1000Mbps SFP porta, od toga 16x PoE porta**<br>**Podržava:**<br>IEEE802.3,IEEE802.3u,IEEE802.3az,IEEE802.3x,IEEE802.3af,IEEE802.3at<br>**Modovi rada:**<br>**Default(Normal mode)**:Svi portovi komuniciraju normalno međusobno<br>**EXTEND(Surveillance mode)**: Distanca prenosa do 250 metara uz brzinu 10Mb/s.<br>**VLAN(Secure mode):** 16 x Downlink portova mogu komunicirati samo sa uplink portovima.<br>**6kV zaštita od prenapona**<br>**PoE Budžet:** 370W<br>**Maksimalna snaga porta:** 250W<br>**Dimenzije:** 440mm x 207mm x 45mm<br>Moguća rek montaža 19'', dolazi uz switch | 336,00 | 280,00 |
| **NSW2010-24T2GC-POE-IN**<br> | 6326 | **NSW2010-24T2GC-POE-IN**<br>**24×100Mbps network ports (RJ45), 2x1000Mbps uplink porta (RJ45), 2x1000Mbps SFP porta, od toga 24 PoE porta**<br>**Podržava:**<br>IEEE802.3,IEEE802.3u,IEEE802.3az,IEEE802.3x,IEEE802.3af,IEEE802.3at<br>**Modovi rada:**<br>**Default(Normal mode)**:Svi portovi komuniciraju normalno međusobno<br>**EXTEND(Surveillance mode)**: Distanca prenosa do 250 metara uz brzinu 10Mb/s.<br>**VLAN(Secure mode**): 24 Downlink portova mogu komunicirati samo sa uplink portovima.<br>**6kV zaštita od prenapona**<br>**PoE Budžet:** 370W<br>**Maksimalna snaga porta:** 30W<br>**Dimenzije:** 440mm x 207mm x 45mm<br>Moguća rek montaža 19'' , dolazi uz switch | 396,00 | 330,00 |

# NOSAČI I PRIBOR UNIVIEW

| NAZIV ARTIKLA | Kat. br. | Karakteristike | CENA EUR (gotovinski) | CENA EUR (racun bez PDV) |
|---|---|---|---|---|
| **TR-A01-IN NPT 3/4** | 6233 | **TR-A01-IN NPT 3/4**<br>Vodootporni uvodnik za mrežne kablove. | 3,60 | 3,00 |
| **TR-JB05-A-IN** | 5871 | **TR-JB05-A-IN**<br>**Nosač za mini bullet kamere**<br>**Dimenzije:** Φ93 × 93 × 39mm<br>**Težina:** 0.2kg<br>**Materijal:** Aluminijum | 14,40 | 12,00 |
| **TR-JB07-D-IN** | 5858 | **TR-JB07-D-IN**<br>**Nosač za kamere serije IPC23XX/222X, IPC74X i IPC252/26X**<br>**Dimenzije:** Φ125mm*125mm*55mm<br>**Težina:** 0.75kg<br>**Materijal:** Aluminijum | 30,00 | 25,00 |
| **TR-JB03-G-IN** | 5879 | **TR-JB03-G-IN**<br>**Nosač za Dome kamere serije IPC32x i IPC31x**<br>**Dimenzije:** φ106.6mm*36mm<br>**Težina:** 0.2kg<br>**Materijal:** Aluminijum | 12,00 | 10,00 |

| | | | | |
|---|---|---|---|---|
| **TR-JB04-C-IN**<br> | 5880 | **TR-JB04-C-IN**<br>**Nosač za Dome kamere serije IPC323X**<br>**Dimenzije:** Φ144.8mm*40mm<br>**Težina:** 0.3kg<br>**Materijal:** Aluminijum | 14,40 | 12,00 |
| **TR-JB03-H-IN**<br> | 5878 | **TR-JB03-H-IN**<br>**Nosač za Dome kamere serije IPC363X Series, IPC36XXS/E i 4MP fisheye**<br>**Dimenzije:** Φ126mm*36mm<br>**Težina:** 0.24kg<br>**Materijal:** Aluminijum | 14,40 | 12,00 |
| **TR-JB05-B-IN**<br> | 5861 | **TR-JB05-B-IN**<br>**Nosač za Dome kamere serije IPC21XX**<br>**Dimenzije:** Φ104.4mm*54.5mm<br>**Težina:** 0.36kg<br>**Materijal:** Aluminijum | 16,80 | 14,00 |
| **TR-JB07/WM03-G-IN**<br>  | 5855 | **TR-JB07/WM03-G-IN**<br>**Zidni nosač za Dome kamere serije IPC36XXL**<br>**Dimenzije:** Φ125mm*125mm*228mm<br>**Težina:** 1kg<br>**Materijal:** Aluminijum | 31,20 | 26,00 |
| **TR-JB07/WM04-B-IN**<br> | 5867 | **TR-JB07/WM04-B-IN**<br>**Zidni nosač za Dome kamere serije IPC323x seriju dome kamera**<br>**Dimenzije:** Φ125mm*125mm*252.5mm<br>**Težina:** 0.98kg<br>**Materijal:** Aluminijum | 33,60 | 28,00 |

| | | | | |
|---|---|---|---|---|
| **TR-JB07/WM03-F-IN**<br> | 5870 | **TR-JB07/WM03-F-IN**<br>**Zidni nosač za Dome kamere serije IPC363X i IPC36XXS/E**<br>**Dimenzije:** Φ125mm*125mm*233mm<br>**Težina:** 0.98kg<br>**Materijal:** Aluminijum | 34,80 | 29,00 |
| **TR-WE45-IN**<br> | 5868 | **TR-WE45-IN**<br>**Zidni nosač za PTZ kamere**<br>**Dimenzije:** 230.3mmx141mmx201.5mm<br>**Težina:** 0.79kg<br>**Materijal:** Aluminijum | 24,00 | 20,00 |
| **TR-WE45-A-IN**<br>  | 6330 | **TR-WE45-A-IN**<br>**Nosač PTZ kamere za unutrašnju i spoljašnu montažu**<br>**Dimenzije:** 216mm x 141mm x 314mm<br>**Težina:** 1.0kg<br>**Materijal:** Aluminijum | 36,00 | 30,00 |
| **TR-CE45-IN**<br> | 5866 | **TR-CE45-IN**<br>**Plafonski nosač za PTZ kamere**<br>**Dimenzije:** Φ116.5mmx239mm<br>**Težina:** 0.67kg<br>**Materijal:** Aluminijum | 26,40 | 22,00 |

# LED PANELI

| NAZIV ARTIKLA | Kat. br. | Karakteristike | CENA EUR (gotovinski) | CENA EUR (racun bez PDV) |
|---|---|---|---|---|
| **MW7504 veće dimenzije**<br> <br>Better Security, Better World. | 6503 | **MW7504 veće dimenzije**<br>**SPOLJAŠNJI LED MODUL**<br><br>**Dimenzije:** 320mm×160mm<br>**Razmak dioda:** 4 mm<br>**Rezolucija:** 80×40<br><br>**SPOLJAŠNJI KABINET**<br><br>**Dimenzije:** 960mm×960mm×105mm<br>**Montirane komponente (D x V):** 3 x 6<br>**Površina ekrana:** 0.9216 m2<br>**Rezolucija:** 240×240<br>**Gustina pixela:** 62500 piksel/m2<br>**Materijal:** liveni aluminijum<br><br>**Osvetljenost:** 5500 cd/m2<br>**Kontrast:** ≥3000:1<br>**Temperatura boje:** 3.500K to 9300K (podesivo)<br>**Ugao gledanja:** Horizontal 140°, Vertical 140°<br>**Grey level:** 14bit<br>**Frame Frequency:** 50/60 Hz<br>**Refresh Rate:** ≥2000 Hz<br>**Napajanje:** 180 to 260 VAC<br>**Potrosnja:** prosečna 320 W/ m2, maksimalna 950 W/ m2<br>**Radna temperatura:** -30□+60℃<br>**Nivo zaštite:** IP65<br>**Radni vek:** ≥100,000 H<br><br>**Napomena: Uredjaj dolazi sklopljen u kućištu dimenzija 960mm×960mm×132mm sa pripadajućim setom dodatne opreme. Bez glavnog dovodnog kabla.** | 106,89 | 89,07 |
| **MW7504 manje dimenzije**<br> <br>Better Security, Better World. | 6755 | **MW7504 manje dimenzije**<br>**SPOLJAŠNJI LED MODUL MW7504**<br>**Dimenzije:** 320mm×160mm<br>**Razmak dioda:** 4 mm<br>**Rezolucija:** 80×40<br>**SPOLJAŠNJI KABINET**<br>**Dimenzija:** 640mm×480mm×105mm<br>**Montirane komponente (D x V):** 3 x 2<br>**Površina ekrana:** 0,3072 m2<br>**Rezolucija:** 240×240<br>**Gustina pixela:** 62500 piksel/m2<br>**Materijal:** liveni aluminijum<br>**Osvetljenost:** 5500 cd/m2<br>**Kontrast:** ≥3000:1<br>**Temperatura boje:** 3.500K to 9300K (podesivo)<br>**Ugao gledanja:** Horizontal 140°, Vertical 140°<br>**Grey level:** 14bit<br>**Frame Frequency:** 50/60 Hz<br>**Refresh Rate:** ≥2000 Hz<br>**Napajanje:** 180 to 260 VAC<br>**Potrosnja:** prosečna 320 W/ m2, maksimalna 950 W/ m2<br>**Radna temperatura:** -30□+60℃<br>**Nivo zaštite:** IP65<br>**Radni vek:** ≥100,000 H | Kontakt | |

# FULL HD MONITORI

| NAZIV ARTIKLA | Kat. br. | Karakteristike | CENA EUR (gotovinski) | CENA EUR (racun bez PDV) |
|---|---|---|---|---|
| **MW3227-L**<br> <br>Better Security, Better World.<br>POUZDANE KOMPONENTE ZA RAD 24/7 1080p FULL HD | 7110 | **MW3227-L**<br>**27" LED MONITOR**<br><br>**Dijagonala ekrana:** 27”<br>**Rezolucija:** 1920×1080@60Hz<br>**Ugao vidljivosti:** Horizontalni 178°, vertikalni 178°<br>**Pozadinsko osvetljenje:** LED Backlight<br>**Osvetljenje:** 250 cd/m²<br>**Kontrast:** 800: 1<br>**Odziv:** 14ms<br>**Boja:** 16.7M<br>**Ulazi:** HDMI, VGA<br>**Napajanje i potrošnja:** DC 12V,3A, 36 W, 0.5W(Standby)<br>**Radna temperatura i vlažnost:** 0°C do 40°C,  20% do 85%<br>**VESA standard** 100x100<br>**Dimenzije:** 614.9 × 455.8 × 224.7<br>**Tezina:** 4.5 Kg<br>**Lista pakovanja:** kabl i adapter za napajanje, upustvo, HDMI kabl<br><br>**Visoko pouzdane komponente za rad 24/7** | 236,40 | 197,00 |
| **MW3232-V-K**<br> <br>Better Security, Better World.<br>POUZDANE KOMPONENTE ZA RAD 24/7 1080p FULL HD | 7584 | **MW3232-V-K**<br>**Dijagonala ekrana:** 31,55”<br>**Rezolucija:** 1920×1080@60Hz<br>**Ugao vidljivosti:** Horizontalni 178°, vertikalni 178°<br>**Pozadinsko osvetljenje:** LED Backlight<br>**Osvetljenje:** 250 cd/m²<br>**Kontrast:** 1200:1<br>**Odziv:** 6,5ms<br>**Boja:** 16.7M<br>**Interfejs:** HDMI, VGA, Audio<br>**Zvučnici:** 2x2W<br>**Napajanje i potrošnja:** AC100V--240V 50/60Hz, ≤ 31.53 (standby ≤0.5W)<br>**Radna temperatura i vlažnost:** 0°C do 50°C,  10% do 85%<br>**VESA:** 4-M3 100mm×100mm<br>**Dimenzije:**  715 × 425 × 44<br>**Težina:** 6,91Kg<br>**Lista pakovanja:** HDMI cable × 1, Power cable × 1, Adapter × 1, Quick guide × 1<br><br>**NAPOMENA: Opciono - zidni nosač HB-5032-H NOSAČ MONITORA 32"**<br>**šifra: 7577**<br>**Visoko pouzdane komponente za rad 24/7** | 370,80 | 309,00 |

# EKRANI ZA VIDEO ZIDOVE

| NAZIV ARTIKLA | Kat. br. | Karakteristike | CENA EUR (gotovinski) | CENA EUR (racun bez PDV) |
|---|---|---|---|---|
| **MW-A55-B1-C**<br> <br>Better Security, Better World. | 7578 | **MW-A55-B1-C**<br>**Ekran:** 55-inča<br>**Širina okvira:** 3.5mm<br>**Rezolucija:** 1920 × 1080@60 Hz<br>**Osvetljenje:** 500 cd/m²<br>**Ugao vidljivosti:** Horizontalni 178°, vertikalni 178°<br>**Kontrast:** 4000:1<br>**Odziv:** 8 ms (G to G)<br>**Video i audio ulazi:** 1×VGA, 1×DVI, 2×HDMI<br>**Napajanje i potrošnja:** 100-240 VAC 50/60 Hz , 210 W<br>**Radna temperatura i vlažnost:** 0°C to 40°C,  20% to 90% RH (bez kondenzacije)<br>**Dimenzije:** 1213.50mm×684.30mm×125.19mm<br>**Težina:** 24.5 Kg<br><br>**Visoko pouzdane komponente za rad 24/7** | 960,00 | 800,00 |

# DEKODERI

| NAZIV ARTIKLA | Kat. br. | Karakteristike | CENA EUR (gotovinski) | CENA EUR (racun bez PDV) |
|---|---|---|---|---|
| **DC5504-E-V2**<br> <br>Better Security, Better World.<br>24/7 POUZDANE KOMPONENTE ZA RAD | 7583 | **DC5504-E-V2**<br>**DEKODER 4 KANALA**<br>**Video izlazi:** 4 kanala<br>**Video ulazi:** 2 HDMI<br>**Video Stream Format:** H.265, H.264, MPEG4, MPEG2, MJPEG<br>**Mogucnost dekodiranja:**<br>4x3840x2160@30□<br>16x1080P@30□<br>36x720P@30□64xD1<br>**Interfejs:**<br>Audio Input 2-ch (Reservation)<br>Audio Output 1-ch (3.5mm)<br>Alarm Input 6(Reservation)<br>Alarm Output 3(Reservation)<br>USB Interface 1*USB 3.0<br>Serial Interface 1*RS-232, 1*RS485<br>Network<br>Interface 1*RJ-45 , 10M/100M/1000M adaptive Ethernet Interfaces<br>**Opšte:**<br>Napajanje i potrošnja:100V ~ 240V AC; 50Hz/60Hz, 20W<br>Radna temperatura i vlaga: -10~55°C, 10 to 90%<br>Dimenzije: 440mm × 339 mm × 44mm<br>Težina: 3,28 kg | 1020,00 | 850,00 |

# NOSAČI

| NAZIV ARTIKLA | Kat. br. | Karakteristike | CENA EUR (gotovinski) | CENA EUR (racun bez PDV) |
|---|---|---|---|---|
| **HB-5032-H**<br> <br>Better Security, Better World. | 7577 | **HB-5032-H**<br>**Zidni nosač za MW3232-E**<br><br>**Boja:** Crna<br>**Materijal:** SGCC<br>**VESA standard**<br>**Dimenzija:** 80mm×428mm×244mm<br>**Težina:** 2,85Kg | 16,80 | 14,00 |

# INTERAKTIVNI EKRANI

| NAZIV ARTIKLA | Kat. br. | Karakteristike | CENA EUR (gotovinski) | CENA EUR (racun bez PDV) |
|---|---|---|---|---|
| **MW3565-T-C2 Interaktivni ekran**<br> <br>Better Security, Better World. | 8407 | **MW3565-T-C2 Interaktivni ekran**<br>**Dijagonala ekrana**: 64.53"<br>**Rezolucija**: 3840×2160<br>**Pozadinsko osvetljenje**: D-LED<br>**Osvetljenje**: 450 cd/m²<br>**Kontrast**: 1200:1<br>**Odziv**: 6 ms<br>**Operativni sistem**: Android 8.0<br>**Integrisana memorija**: RAM 3GB DDR4 ; ROM 16GB<br>**Zvučnici**: 2×15W<br>**Interfejsi**: Ulazni: HDMI × 3, DP ×1, VGA ×1, LAN ×2, PC-AUDIO IN ×1, YPBPR ×1, AV ×1, TOUCH-USB ×2, OPS ×1, Android USB×2, Public USB×2 ; Izlazni: HDMI×1, AV×1, S/PDIF×1, AUDID OUT×1<br>**Napajanje i potrošnja**: 100 to 240 V AC<br>**Radna temperatura i vlažnost**: -10□60℃<br>**Dimenzije**: 1506.3(W) × 901.3 (H) ×96.1(D)<br>**Težina**: 42Kg | 1320,00 | 1100,00 |
| **MW3575-T-C2 Interaktivni ekran**<br> <br>Better Security, Better World. | 8406 | **MW3575-T-C2 Interaktivni ekran**<br>**Dijagonala ekrana**: 74.52 "<br>**Rezolucija**: 3840×2160<br>**Pozadinsko osvetljenje**: D-LED<br>**Osvetljenje**: 450 cd/m²<br>**Kontrast**: 1200:1<br>**Odziv**: 1.07B<br>**Operativni sistem**: Android 8.0<br>**Integrisana memorija**: RAM 3GB DDR4 ; ROM 16GB<br>**Zvučnici**: 2×15W<br>**Interfejsi**: Ulazni -HDMI ×3, DP ×1, VGA ×1, LAN ×2, PC-AUDIO IN ×1, YPBPR ×1, AV ×1, TOUCH-USB ×2, OPS ×1, Android USB×2, Public USB×2□Izlazni: HDMI×1, AV×1, S/PDIF×1, AUDID OUT×1<br>**Napajanje i potrošnja**: 100 to 240 V AC, ≤400 W<br>**Radna temperatura i vlažnost**: 0°C ~ 40 °C, 20%~80%<br>**Dimenzije**: 1735.98(W)×1034.52(H)×103.75(D)<br>**Težina**: 58Kg | 1620,00 | 1350,00 |
| **MW3586-T-C2 Interaktivni ekran**<br> <br>Better Security, Better World. | 8405 | **MW3586-T-C2 Interaktivni ekran**<br>**Dijagonala ekrana**: 85.6 "<br>**Rezolucija**: 3840×2160<br>**Pozadinsko osvetljenje**: D-LED<br>**Osvetljenje**: 400 cd/m²<br>**Kontrast**: 1200:1<br>**Odziv**: 8 ms<br>**Operativni sistem**: Android 8.0<br>**Integrisana memorija**: RAM 3GB DDR4 ; ROM 16GB<br>**Zvučnici**: 2×15W<br>**Interfejsi**: Ulazni HDMI ×3, DP ×1, VGA ×1, LAN ×2, PC-AUDIO IN ×1, YPBPR ×1, AV ×1, TOUCH-USB ×2, OPS ×1, Android USB×2, Public USB×2□Izlazni: HDMI×1, AV×1, S/PDIF×1, AUDID OUT×1<br>**Napajanje i potrošnja**: 100 to 240 V AC, ≤500 W<br>**Radna temperatura i vlažnost**: 0°C ~ 40 °C, 20%~80%<br>**Dimenzije**: 1989.18(W)×1080.22(H)×119.7(D)<br>**Težina**: 77Kg | 2136,00 | 1780,00 |